
DELTALIGHT




LOGIC MINI W R

REFERENCE 304 30 12 A

AVAILABLE IN
ALU GREY 304 30 12 A
BLACK 304 30 12 B
FLEMISH BRONZE OUTDOOR 304 30 12 FBRX
ANTHRACITE 304 30 12 N
WHITE 304 30 12 W





View on website

General info	
LOCATION	indoor-outdoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	round - 55
RECESSED DEPTH (MM)	50
THICKNESS OF MOUNTING SURFACE (MM)	min.12
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 24V-DC

Electrical info	
ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 0,6W / 3000K / 40lm
LED TECHNICS (LIGHT SOURCE)	40lm // 0,6W // 67lm/W
LED TECHNICS (LUMINAIRE)	4lm // 0,7W // 5lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CONCRETE BOX 188

For detailed installation instructions, please consult the manual : **304_30_12_HAND.pdf**

DELTALIGHT

LOGIC MINI W R

304 30 12 A


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 24 20 LED POWER SUPPLY 24V-DC / 20W — 30 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 60



300 89 24 40 LED POWER SUPPLY 24V-DC / 40W — 60 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 55



300 89 24 60 LED POWER SUPPLY 24V-DC / 60W — 90 ☐


Dimtype: non-dimmable

Cutout dimension (mm): 55



300 89 24 61 LED POWER SUPPLY 24V-DC / 60W DIN — 90 ☐


Dimtype: non-dimmable



300 89 24 80 ED1 LED POWER SUPPLY 24V-DC / 80W DIM1 — 120 ☐

Dimtype: 1-10V


Cutout dimension (mm): 75



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W — 225 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 75



21012 0160 LED POWER SUPPLY 24V-DC / 24W — 36 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 55

DELTALIGHT

LOGIC MINI W R

304 30 12 A

Concrete boxes



270 11 188 CONCRETE BOX 188

Cutout dimension (mm): 67

Notes: