
DELTALIGHT




DOT.COM M4 TRIMLESS 92749

REFERENCE 424 512 04 923 C

AVAILABLE IN
BLACK 424 512 04 923 B
CHROMED 424 512 04 923 C
FLEMISH GOLD 424 512 04 923 FG





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	60
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	4 x REFLECTOR WFL-49° EXCL.LED POWER SUPPLY 500mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	EAC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 5,7W / CRI>90 (R9: 50) / 2700K / 631lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
BEAMANGLE	49°
LED TECHNICS (LIGHT SOURCE)	631lm // 5,7W // 111lm/W
LED TECHNICS (LUMINAIRE)	454lm // 6,6W // 69lm/W

Requirements

MOUNTING KIT DOT.COM M4 TRIMLESS
LED POWER SUPPLY 500mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual : **424_512_04_XXX_HAND.pdf**

DELTALIGHT

DOT.COM M4 TRIMLESS 92749

424 512 04 923 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **Plasterboard**	424 512 04 00 - MOUNTING KIT DOT.COM M4 TRIMLESS	Required
 **Stucanet**	424 512 04 00 - MOUNTING KIT DOT.COM M4 TRIMLESS	Required
 **Concrete + plaster**	424 512 04 00 - MOUNTING KIT DOT.COM M4 TRIMLESS	Required
 **Lintel + plaster**	424 512 04 00 - MOUNTING KIT DOT.COM M4 TRIMLESS	Required
 **Hollow-core slab + plaster**	424 512 04 00 - MOUNTING KIT DOT.COM M4 TRIMLESS	Required
 **Stretched ceiling**	15212 0180 - MOUNTING KIT DOT.COM M4 TRIMLESS WSC	Required
	15212 0110 - MOUNTING KIT DOT.COM M4 TRIMLESS CSC	Required


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 3

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 3

Dimtype: DALI


Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 3

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

DOT.COM M4 TRIMLESS 92749


424 512 04 923 C



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 4

Dimtype: mains (phase cut-off) or push button


Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 6(6)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 4(2)

Dimtype: 1-10V or push button


Cutout dimension (mm): 72



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 4(2)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 9(7)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 3(2)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 3(2)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV — 3->7

Dimtype: non-dimmable


Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER — 3

Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 — 4


Dimtype: 1-10V

Cutout dimension (mm): 54

DELTALIGHT

DOT.COM M4 TRIMLESS 92749


424 512 04 923 C



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 — 4

Dimtype: DALI


Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL — 6(6)

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 4

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 — 2->2

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 — 3->4

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 3

Dimtype: DALI

Cutout dimension (mm): 30

Mounting kits



424 512 04 00 MOUNTING KIT DOT.COM M4 TRIMLESS


Cutout dimension (mm): 127 x 36

DELTALIGHT


DOT.COM M4 TRIMLESS 92749

424 512 04 923 C

Mounting kits stretched ceiling



15212 0110 MOUNTING KIT DOT.COM M4 TRIMLESS CSC



15212 0180 MOUNTING KIT DOT.COM M4 TRIMLESS WSC

Notes: