




TWEETER M ON 2 93033 DIM8

418 51 812 932 ED8 B-C

AVAILABLE IN
BLACK-CHROMED 418 51 812 932 ED8 B-C
WHITE-WHITE 418 51 812 932 ED8 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	2178lm // 17,2W // 127lm/W
LED TECHNICS (LUMINAIRE)	1735lm // 19,8W // 88lm/W

For detailed installation instructions, please consult the manual : [418_51_812_XXX_HAND.pdf](#)

TWEETER M ON 2 93033 DIM8

418 51 812 932 ED8 B-C

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



Notes: