

**OML50 - LED ARRAY DU HO
CORNER L 940 DIM5**

31065 9405

[Bekijk op website](#)**Algemene info**

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.4
INFO	CLUSTER DOWN: 4029lm/m CLUSTER UP: 2776lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: 2 x (LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm) UP: 2 x (LED cluster 12,1W / CRI>90 (R9: 50) / 4000K / 1821lm)
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 5286lm // 32,6W // 162lm/W UP: 3642lm // 24,2W // 151lm/W

Opties

WIRELESS CONTROL DIM5

Notes: