





KIX II PIN 92755

13537 9230 N

AVAILABLE IN
ALU GREY 13537 9230 A
ANTHRACITE 13537 9230 N
PINE GREEN 13537 9230 PGR



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1.2
ADJUSTABILITY	180° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-55° INCL.1 x CABLE H05 RN-F 2 x 1mm² 2m INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	55°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	618lm // 6,7W // 93lm/W

Options	
CBOX	
IP68 CONNECTION KIT	
IP68 CONNECTOR 3P	

Accessories	
KAP KIX	
HONEYCOMB KIX	

For detailed installation instructions, please consult the manual : [13537_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142

☐

216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐

Light altering devices



232 10 00 N KAP KIX N

☐

232 10 03 N HONEYCOMB KIX N

☐

Notes: