



ENTERO SQ-L TRIMLESS 92718



28535 9210 B

AVAILABLE IN

BLACK 28535 9210 B

FULL WHITE 28535 9210 FW

GOLD COLOURED 28535 9210 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	165
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCLLED POWER SUPPLY 350-1050mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,3-36,5W / CRI>90 (R9: 60) / 2700K / 1561-4380lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	4380lm // 36,5W // 120lm/W
LED TECHNICS (LUMINAIRE)	3664lm // 42W // 87lm/W

Remarks

Max.900mA when using 1 accessory; max 800mA when using 2 accessories

Requirements

MOUNTING KIT ENTERO SQUARE L

LED POWER SUPPLY 350 / 500 / 700 / 1050mA-DC DIM (Remote)

Accessories

ENTERO L HONEYCOMB

ENTERO L LINEAR SPREAD LENS

ENTERO L SPREAD LENS

ENTERO L SOFTENING LENS

ENTERO L GLASS SBL

ENTERO SQ-L TRIMLESS 92718



28535 9210 B

For detailed installation instructions, please consult the manual : [28535_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY











Ceiling Type	Mounting Kit	
 System ceiling	 28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 Plasterboard	 28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 Stucanet	 28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 Wood	 28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 Concrete + plaster	 28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 Lintel + plaster	 28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 Hollow-core slab + plaster	 28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 Stretched ceiling	 28400 0120 - MOUNTING KIT ENTERO SQ-L CSC	Required
	 28400 0180 - MOUNTING KIT ENTERO SQ-L WSC	Required

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	2(2) 2(2) 2(1) - ☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	1 ☐

ENTERO SQ-L TRIMLESS 92718

28535 9210 B


	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	1	☐
	300 90 136 LED POWER SUPPLY MULTI-POWER HC DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 90	1(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	1	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	1(1)	☐
	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	1(0)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	1(0)	☐

DELTALIGHT

ENTERO SQ-L TRIMLESS 92718

28535 9210 B

Mounting kits




28400 0060 MOUNTING KIT ENTERO SQ-L

Cutout dimension (mm): 142 x 142

☐

Mounting kits stretched ceiling



28400 0120 MOUNTING KIT ENTERO SQ-L CSC

☐



28400 0180 MOUNTING KIT ENTERO SQ-L WSC


☐

Light altering devices



28500 0130 ENTERO L LINEAR SPREAD LENS

☐



28500 0140 ENTERO L SPREAD LENS

☐




28500 0150 ENTERO L SOFTENING LENS

☐



28500 0160 ENTERO L GLASS SBL

☐




28500 0170 B ENTERO L HONEYCOMB SINGLE USE B

☐

DELTALIGHT

ENTERO SQ-L TRIMLESS 92718

28535 9210 B



28500 0180 B ENTERO L HONEYCOMB DOUBLE USE B



Notes: