
DELTALIGHT




MINIGRID IN TRIMLESS 1 92750

REFERENCE 100009 9230 W-B

AVAILABLE IN
BLACK-BLACK 100009 9230 B-B
BLACK-WHITE 100009 9230 B-W
WHITE-BLACK 100009 9230 W-B
WHITE-WHITE 100009 9230 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	85
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	REFLECTOR FL-50° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	50°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	838lm // 10W // 85lm/W

Requirements

MINIGRID IN 1 MOUNTING KIT
MINIGRID IN 1 MOUNTING KIT LARGE
CONCRETE PACK MGIT 1
LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual : **100009_XXX0_HAND.pdf**

MINIGRID IN TRIMLESS 1 92750

100009 9230 W-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	202 71 95 01 - MINIGRID IN 1 MOUNTING KIT	Required
 **Plasterboard**	202 71 95 01 - MINIGRID IN 1 MOUNTING KIT	Required
 **Stucanet**	202 71 95 01 - MINIGRID IN 1 MOUNTING KIT	Required
	202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 **Concrete**	202 71 96 01 - CONCRETE PACK MGIT 1	Required
 **Concrete + plaster**	202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 **Lintel + plaster**	202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 **Hollow-core slab**	202 71 96 01 - CONCRETE PACK MGIT 1	Required
 **Hollow-core slab + plaster**	202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 **Stretched ceiling**	15212 0120 - MOUNTING KIT MINIGRID IN 1 CSC	Required


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 — 1

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 1

Dimtype: DALI

Cutout dimension (mm): 45

MINIGRID IN TRIMLESS 1 92750


100009 9230 W-B



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL — 1

Dimtype: non-dimmable


Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL — 1

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 1

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 1

Dimtype: DALI


Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 1

Dimtype: non-dimmable


Cutout dimension (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 1

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 2 | 2

Dimtype: mains (phase cut-off) or push button


Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 4(4) | 4(4)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 2(1) | 2(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72




300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 2

Dimtype: 1-10V or DALI or push button

MINIGRID IN TRIMLESS 1 92750


100009 9230 W-B



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 2(2) | 2(1)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 2->6(6) | 6(4)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 3(2) | 2(1)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 2(2) | 2(1)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 3->3 | 2->3

Dimtype: non-dimmable


Cutout dimension (mm): 90



21012 004W LED POWER SUPPLY MULTI-POWER WDL 3(3) | 3(3)

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 3 | 3

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 2->3


Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55

DELTALIGHT

MINIGRID IN TRIMLESS 1 92750


100009 9230 W-B



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 2

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 48



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 — 2(2)

Dimtype: non-dimmable


Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 — 2(1)

Dimtype: non-dimmable


Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 30




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 30


Concrete packs



202 71 96 01 CONCRETE PACK MGIT 1

Cutout dimension (mm): 160 x 160

Mounting kits



202 71 95 01 MINIGRID IN 1 MOUNTING KIT

Cutout dimension (mm): 130 x 130



202 71 95 01L MINIGRID IN 1 MOUNTING KIT LARGE


Cutout dimension (mm): 200

DELTALIGHT

MINIGRID IN TRIMLESS 1 92750

100009 9230 W-B

Mounting kits stretched ceiling



15212 0120 MOUNTING KIT MINIGRID IN 1 CSC

Notes: