



M26L - SPY 391 SOFT 93040 DIM5

23438 9035 BROB

AVAILABLE IN

SCHWARZ 23438 9035 B

ALU GEBÜSTET 23438 9035 BRA

GEBÜSTETES ANTHRAZIT 23438 9035 BRAT

GEBÜSTETES KUPFER 23438 9035 BRCU

GEBÜSTETES GOLD 23438 9035 BRG

GEBÜSTETE ALTE BRONZE 23438 9035 BROB

FLEMISH BRONZE 23438 9035 FBR

FLEMISH GOLD 23438 9035 FG

GOLDFARBEN 23438 9035 GC

KLAVIER SCHWARZ 23438 9035 PB

WEISS 23438 9035 W



[View on website](#)



General info

LOCATION	innenbereich
INSTALLATION	Niederspannungssysteme Niederspannungssysteme montiert
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° schwenkbar, 360° drehbar
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	505lm // 6,9W // 73lm/W

Requirements

SPY 39 TUBE

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23438_XXX5_HAND.pdf](#)

M26L - SPY 391 SOFT 93040 DIM5

23438 9035 BROB

FINISH YOUR SPECIFICATION


LED Betriebsgeräte

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

8

Dimtype: nicht dimmbar



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: nicht dimmbar



21012 0230 LED POWER SUPPLY 48V-DC / 100W

8

Dimtype: nicht dimmbar

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

17

Dimtype: nicht dimmbar

Cutout dimension (mm): 40

Beenden Sie Ihr Produkt



24144 0010 B SPY 39 TUBE B

24144 0010 FBR SPY 39 TUBE FBR

24144 0010 FG SPY 39 TUBE FG

24144 0010 GC SPY 39 TUBE GC

24144 0010 W SPY 39 TUBE W

M26L - SPY 391 SOFT 93040 DIM5

23438 9035 BROB




24144 0070 SPY 39 TUBE SBL




COMPATIBLE COMPOSABLES


SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
--	-------------------




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: