
DELTALIGHT




ENTERO RD-M TRIMLESS WALLWASH TW 940

REFERENCE 28468 9000 W

AVAILABLE IN
BLACK 28468 9000 B
GOLD COLOURED 28468 9000 GC
WHITE 28468 9000 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	95
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.16
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WALLWASH EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	979lm // 9W // 109lm/W
LED TECHNICS (LUMINAIRE)	796lm // 10,4W // 77lm/W

Requirements

MOUNTING KIT ENTERO ROUND M
LED POWER SUPPLY 500mA-DC TW (Remote)

For detailed installation instructions, please consult the manual : **28468_XXX0_HAND.pdf**

DELTALIGHT

ENTERO RD-M TRIMLESS WALLWASH TW 940

28468 9000 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Plasterboard**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Stucanet**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Concrete + plaster**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Lintel + plaster**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Hollow-core slab + plaster**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Stretched ceiling**	28400 0080 - MOUNTING KIT ENTERO RD-M CSC	Required
	28400 0140 - MOUNTING KIT ENTERO RD-M WSC	Required


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 85

Mounting kits



28400 0020 MOUNTING KIT ENTERO RD-M O.F.A.


Cutout dimension (mm): 127

DELTALIGHT

ENTERO RD-M TRIMLESS WALLWASH TW 940

28468 9000 W

Mounting kits stretched ceiling



28400 0080 MOUNTING KIT ENTERO RD-M CSC



28400 0140 MOUNTING KIT ENTERO RD-M WSC

Notes: