

## OML50 - LED ARRAY DU HO CORNER T 930 DIM5

31066 9305


[Bekijk op website](#)


### Algemene info

|                               |  |
|-------------------------------|--|
| <b>LOCATIE</b>                | binnen   |
| <b>STOF EN WATERDICHTHEID</b> | IP20   |
| <b>GEWICHT (KG)</b>           | 1.4  |
| <b>INFO</b>                   | CLUSTER DOWN: 3863lm/m<br>CLUSTER UP: 2663lm/m<br>INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT |

### Elektrische info

|                        |                      |
|------------------------|----------------------|
| <b>INGANGSSPANNING</b> | 220-240V / 0 50-60Hz |
| <b>KLASSE</b>          | I                    |
| <b>VOEDING</b>         | YES                  |
| <b>DIM TYPE</b>        | DALI                 |
| <b>ENERGIE KLASSE</b>  | D                    |
| <b>CERTIFICATEN</b>    | EPD, RCM             |

### Info lichtbron

|                                 |  |
|---------------------------------|--|
| <b>LIGHTSOURCE NAME</b>         | LED  |
| <b>LICHTBRON</b>                | DOWN: 2 x (LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm)<br>UP: 2 x (LED cluster 12,1W / CRI>90 (R9: 50) / 3000K / 1747lm) |
| <b>TM-30-15 WAARDEN</b>         | Rf: 92 / Rg: 100   |
| <b>SDCM</b>                     | SDCM3  |
| <b>RISK-GROEP</b>               | RG1  |
| <b>LM80</b>                     | L80 > 60000  |
| <b>LED TECHNIEK (LICHTBRON)</b> | DOWN: 5068lm // 32,6W // 155lm/W<br>UP: 3494lm // 24,2W // 145lm/W   |

### Opties

WIRELESS CONTROL DIM5

Notes: