




HALOSCAN ON 1 MP 93021 DIM8

23147 9328 W-W

AVAILABLE IN
BLACK-BLACK 23147 9328 B-B
BLACK-GOLD COLORED 23147 9328 B-GC
WHITE-WHITE 23147 9328 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS FL-21° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	21°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	850lm // 9,9W // 86lm/W

Accessories	
HALOSCAN HONEYCOMB	
HALOSCAN LINEAR SPREAD LENS	
HALOSCAN KAP MP	

For detailed installation instructions, please consult the manual : [23147_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



Ø72

23110 0040 HALOSCAN LINEAR SPREAD LENS

☐



Ø72

23110 0050 B HALOSCAN HONEYCOMB B

☐



Ø82

23110 0060 B HALOSCAN KAP MP B

☐

23110 0060 W HALOSCAN KAP MP W

☐

Notes: