





HALOSCAN ON 1 MP 93021 DIM8

23147 9328 W-W

AVAILABLE IN
NOIR-NOIR 23147 9328 B-B
NOIR-COULEUR OR 23147 9328 B-GC
BLANC-BLANC 23147 9328 W-W



[View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° à 45° inclinable, 355° rotatif
INFORMATION	LENS FL-21° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	fin de phase
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	21°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	850lm // 9,9W // 86lm/W

Accessories

HALOSCAN HONEYCOMB
 HALOSCAN LINEAR SPREAD LENS
 HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : [23147_XXX8_HAND.pdf](#)

DELTALIGHT

HALOSCAN ON 1 MP 93021 DIM8

23147 9328 W-W

FINISH YOUR SPECIFICATION

modifier les dispositifs de lumière



Ø72

23110 0040 HALOSCAN LINEAR SPREAD LENS

☐



Ø72

23110 0050 B HALOSCAN HONEYCOMB B

☐



Ø82

23110 0060 B HALOSCAN KAP MP B

☐

23110 0060 W HALOSCAN KAP MP W

☐

Notes: