



LOGIC MINI W R

304 30 12 W

AVAILABLE IN



ALU GREY 304 30 12 A

BLACK 304 30 12 B

FLEMISH BRONZE OUTDOOR 304 30 12 FBRX

ANTHRACITE 304 30 12 N

WHITE 304 30 12 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	round - 55
RECESSED DEPTH (MM)	50
THICKNESS OF MOUNTING SURFACE (MM)	min.12
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 24V-DC

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 0,6W / 3000K / 40lm
LED TECHNICS (LIGHT SOURCE)	40lm // 0,6W // 67lm/W
LED TECHNICS (LUMINAIRE)	4lm // 0,7W // 5lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CONCRETE BOX 188

For detailed installation instructions, please consult the manual : [304_30_12_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 24 20

LED POWER SUPPLY 24V-DC / 20W

30

Dimtype: non-dimmable

Cutout dimension (mm): 60




300 89 24 40

LED POWER SUPPLY 24V-DC / 40W

60

Dimtype: non-dimmable

Cutout dimension (mm): 55




300 89 24 60

LED POWER SUPPLY 24V-DC / 60W

90

Dimtype: non-dimmable

Cutout dimension (mm): 55




300 89 24 61

LED POWER SUPPLY 24V-DC / 60W DIN

90

Dimtype: non-dimmable




300 89 24 80 ED1

LED POWER SUPPLY 24V-DC / 80W DIM1

120

Dimtype: 1-10V

Cutout dimension (mm): 75




300 89 24 150

LED POWER SUPPLY 24V-DC / 150W

225

Dimtype: non-dimmable

Cutout dimension (mm): 75



21012 0160

LED POWER SUPPLY 24V-DC / 24W

36

Dimtype: non-dimmable


Cutout dimension (mm): 55

DELTALIGHT

LOGIC MINI W R

304 30 12 W

Concrete boxes



270 11 188 CONCRETE BOX 188



Cutout dimension (mm): 67

Notes: