DELTALIGHT



OML50 - LED ARRAY DU HO 2624mm 930

REFERENCE 31038 9300

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.6
INFORMATION	CLUSTER DOWN: 3863lm/m CLUSTER UP: 2663lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 65,3W / CRI>90 (R9: 50) / 3000K / 10138lm UP: LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 10138lm // 65,3W // 155lm/W UP: 6989lm // 48,4W // 145lm/W

Notes:

Delta Light NV may revise the information and technical data at any time without notice. Version: 08/10/2026