

LOGIC LINEAR ON 440 92725 DIM5

30827 9225 A

AVAILABLE IN



ALU GREY 30827 9225 A

BLACK 30827 9225 B

FLEMISH BRONZE OUTDOOR 30827 9225 FBRX

ANTHRACITE 30827 9225 N

WHITE 30827 9225 W



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1
INFORMATION	8 x LENS FL-25° EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,4W / CRI>90 (R9: 55) / 2700K / 1644lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	25°
LED TECHNICS (LIGHT SOURCE)	1644lm // 14,4W // 111lm/W
LED TECHNICS (LUMINAIRE)	1361lm // 16,6W // 82lm/W

Requirements

WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC


Options


THROUGH WIRING SET IP68

For detailed installation instructions, please consult the manual : [30827_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current

	21032 0390 LED POWER SUPPLY 48V-DC / 90W Dimtype: non-dimmable Cutout dimension (mm): 75	5
--	---	------------------------

Fixation components		
	30810 0040 LOGIC LINEAR 880 BOX EXTEND	
	30810 0040 INOX WALL BRACKET SET 60 INOX	
	30810 0040 N WALL BRACKET SET 60 N	
	30810 0050 INOX WALL BRACKET SET 100 INOX	
	30810 0050 N WALL BRACKET SET 100 N	
	30810 0060 INOX WALL BRACKET SET 200 INOX	
	30810 0060 N WALL BRACKET SET 200 N	

DELTALIGHT

LOGIC LINEAR ON 440 92725 DIM5

30827 9225 A



30810 0070 INOX FLOOR BRACKET SET INOX

☐

Electric connection parts



30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m

☐

30810 0090 IP68 CABLE + CONNECTOR 5P - 2m

☐

30810 0100 THROUGH WIRING SET IP68 440

☐

Notes: