



OML50 - LED ARRAY DU HO 2624mm 940

31038 9400



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.6
INFO	CLUSTER DOWN: 4029lm/m CLUSTER UP: 2776lm/m INCLLED POWER SUPPLY CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 65,3W / CRI>90 (R9: 50) / 4000K / 10573lm UP: LED cluster 48,4W / CRI>90 (R9: 50) / 4000K / 7283lm
TM-30-15 WAARDEN	Rf: 90 / Rg: 101
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 10573lm // 65,3W // 162lm/W UP: 7283lm // 48,4W // 151lm/W

Notes: