



COMPO S TW 94020

9 15714 9020 B


AVAILABLE IN

SCHWARZ 9 15714 9020 B

CHROM 9 15714 9020 C

DUNKLES CHROM 9 15714 9020 DC

WEISS 9 15714 9020 W



[View on website](#)



General info

LOCATION	innenbereich
INSTALLATION	Decke Einbau
CUTOUT SHAPE/SIZE (MM)	rund - 90
RECESSED DEPTH (MM)	85
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.128
ADJUSTABILITY	0° to 30° schwenkbar, 355° drehbar

Electrical info

CLASS	III
DIM TYPE	Abhängig von der Art der externen Stromversorgung
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,3W / CRI>90 / 1800K-4000K / 604lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 56000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	604lm // 5,3W // 113lm/W
LED TECHNICS (LUMINAIRE)	362lm // 6,1W // 59lm/W

Requirements

LED POWER SUPPLY 150 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B

COMPO S LINEAR SPREAD LENS

COMPO S SPREAD LENS

COMPO S SOFTENING LENS

COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : [9_15714_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Netzteil

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 5700 LED POWER SUPPLY MULTIPOWER 12W DALI DT8 150mA

1

Mounting Kit



15710 0010 B MOUNTING KIT COMPO S TRIM B

Cutout dimension (mm): 55

15710 0010 W MOUNTING KIT COMPO S TRIM W



15710 0040 MOUNTING KIT COMPO S TRIMLESS

Cutout dimension (mm): 55

Licht veredelndes Zubehör

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

15710 0110 COMPO S LINEAR SPREAD LENS

DELTALIGHT

COMPO S TW 94020

9 15714 9020 B

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS



Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS



Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL



Cutout dimension (mm): 26,5

Notes: