



M26L - SPY 391 SOFT 93020 MDL

23437 9020 FBR

AVAILABLE IN

NEGRO 23437 9020 B

ALU CEPILLADO 23437 9020 BRA

ANTRACITA CEPILLADO 23437 9020 BRAT

COBRE CEPILLADO 23437 9020 BRCU

ORO CEPILLADO 23437 9020 BRG

BRONCE VIEJO CEPILLADO 23437 9020 BROB


FLEMISH BRONZE 23437 9020 FBR

FLEMISH GOLD 23437 9020 FG

ORO COLOREADO 23437 9020 GC

NEGRO PIANO 23437 9020 PB

BLANCO 23437 9020 W



[View on website](#)



General info

LOCATION	interior
INSTALLATION	Sistemas de baja tensión Montado en sistemas de baja tensión
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° giratorio, 360° orientable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1 a 10 v o DALI o SWITCH DE PRESION
ENERGY CLASS	F
CERTIFICATES	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	508lm // 6,9W // 74lm/W

Requirements

SPY 39 TUBE

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [23437_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Cable de alimentación

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

16

Dimtype: WDL = Regulable inalámbrico

SMART 48

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

16

Dimtype: 1 a 10 V o DALI o switch de presion



300 90 012 SMART 48 MODULATOR WD

16

Dimtype: WDL = Regulable inalámbrico

Fuente de Alimentación LED

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

8

Dimtype: no dimerizable


DELTALIGHT

M26L - SPY 391 SOFT 93020 MDL


23437 9020 FBR

	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	20	☐
Dimtype: no dimerizable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	8	☐
Dimtype: no dimerizable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	17	☐
Dimtype: no dimerizable			
Cutout dimension (mm): 40			

Termina tu producto

	24144 0010 B SPY 39 TUBE B	☐
24144 0010 FBR SPY 39 TUBE FBR		☐
24144 0010 FG SPY 39 TUBE FG		☐
24144 0010 GC SPY 39 TUBE GC		☐
24144 0010 W SPY 39 TUBE W		☐
	24144 0070 SPY 39 TUBE SBL	☐

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
	
23358 0000 SLM26L - PROFILE	


DELTALIGHT

M26L - SPY 391 SOFT 93020 MDL


23437 9020 FBR



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: