



TIGA



A medium sized rectangular lighting fixture, delivering a pleasant up and downward light effect on your wall. As a wall surface mounted unit, the TIGA is perfect for both residential use or for hospitality usage in hotels and restaurants.

Specification	
Installation Method:	1/2" EMT or 4" J-Box
Adjustability:	Fixed
Rating:	IP20 & IP65, see Ordering below

Performance	
LED Maintenance:	L90>50,000h
McAdam Step:	1
CRI:	90
*SP:	7W

Delivered Lumens	2700K	3000K	3500K
Tiga IP20:	405Lm	423Lm	439Lm
Tiga IP65 WW:	491Lm	513Lm	532Lm
Tiga IP65 WN:	364Lm	381Lm	395Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: TIG2-WWO-B-MMAT-SP27-SFND-120

Luminaire	Rating	Optic	Style	Finish	Power*	CCT	Installation	Controls***
TIG TIGA	6 IP65 for exterior use	WW Wide Up/Wide Down WN Wide Up / Narrow Down	L Lensed	A Alu Grey B Black FBRX Flemish Bronze G Grey Brown N Anthracite (Dark Grey) W White	SP Standard Power	27 2700K 30 3000K 35 3500K	ON Surface mounted to 4" junction box or 1/2" EMT install	ND-120 Non-dim 120V
	2 IP20 for exterior use	WW Wide Up / Wide Down Optional beam accessory available	O Open	B-MMAT Black-Gold Matte W-W White-White				

*** Contact factory for additional dimming options.

Related Products

Momba, Mono, Montur (wall & bollards), Walker (wall & bollards)

DELTALIGHT


www.deltalight.com






Finish Options


TIGA



TIGA IP20




BLACK-MMAT




WHITE-WHITE


TIGA IP65 WW



ALU GREY



BLACK




FLEMISH BRONZE



GREY BROWN




ANTHRACITE




WHITE


TIGA IP65 WN



ALU GREY



BLACK



FLEMISH BRONZE



GREY BROWN



ANTHRACITE




WHITE-WHITE

Accessories

TIGA V-PLATE
223 753 01 BTIGA V-PLATE
223 753 01 W


Photometric Data

TIGA IP65 WW




Wide/Wide

TIGA IP65 WN



Wide/Narrow

TIGA IP20 WW



Wide/Wide

Driver Options

ND

- Dimming Control NON DIMMABLE
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥80

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.

DELTALIGHT