





## LASS-OH! L330-6 93034

24819 9320 B

AVAILABLE IN  
**BLACK** 24819 9320 B  
**GOLD COLOURED** 24819 9320 GC



[View on website](#)



| General info                |                                                                                                                                                                                             |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOCATION                    | indoor                                                                                                                                                                                      |
| INSTALLATION                | Ceiling Suspended                                                                                                                                                                           |
| INGRESS PROTECTION          | IP20                                                                                                                                                                                        |
| WEIGHT (KG)                 | 1.4                                                                                                                                                                                         |
| ADJUSTABILITY               | non adjustable                                                                                                                                                                              |
| INFORMATION                 | INCL.6 x DOT.COM S6 modules<br>per module: 6 x REFLECTOR FL-34°<br>EXCL.LED POWER SUPPLY 1050mA-DC<br>INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m<br>INCL.1 x CABLE 2 x 0.75mm <sup>2</sup> |
| Electrical info             |                                                                                                                                                                                             |
| CLASS                       | III                                                                                                                                                                                         |
| DIM TYPE                    | depending on power supply                                                                                                                                                                   |
| ENERGY CLASS                | E                                                                                                                                                                                           |
| CERTIFICATES                | CB, EAC, ENEC                                                                                                                                                                               |
| Lightsource info            |                                                                                                                                                                                             |
| LIGHTSOURCE NAME            | LED                                                                                                                                                                                         |
| LIGHTSOURCE                 | 6 x (LED cluster 6,1W / CRI>90 (R9: 50) / 3000K / 683lm)                                                                                                                                    |
| TM-30 VALUES                | Rf: 90 / Rg: 101                                                                                                                                                                            |
| SDCM                        | SDCM3                                                                                                                                                                                       |
| LM80                        | L80 > 60000                                                                                                                                                                                 |
| BEAMANGLE                   | 34°                                                                                                                                                                                         |
| LED TECHNICS (LIGHT SOURCE) | 4098lm // 36,6W // 112lm/W                                                                                                                                                                  |
| LED TECHNICS (LUMINAIRE)    | 3239lm // 42,1W // 77lm/W                                                                                                                                                                   |

### Requirements

LASS-OH! POWERBOX  
 LED POWER SUPPLY 1050mA-DC DIM

### Options

CABLE BASE R / S  
 COVERSET R 62-90-100 / S 62-80-90  
 CONNECTION ST / CONNECTION TRIMLESS  
 SUSPENSION ST / SUSPENSION TRIMLESS


### Accessories

JIHA S / R

For detailed installation instructions, please consult the manual : [24819\\_XXXX\\_HAND.pdf](#)



FINISH YOUR SPECIFICATION

Current supply

|                                                                                    |                                       |                          |
|------------------------------------------------------------------------------------|---------------------------------------|--------------------------|
|    | <b>203 99 55 ANO</b> CABLE BASE R ANO | <input type="checkbox"/> |
|                                                                                    | <b>203 99 55 B</b> CABLE BASE R B     | <input type="checkbox"/> |
|                                                                                    | <b>203 99 55 W</b> CABLE BASE R W     | <input type="checkbox"/> |
|  | <b>203 99 56 ANO</b> CABLE BASE S ANO | <input type="checkbox"/> |
|                                                                                    | <b>203 99 56 B</b> CABLE BASE S B     | <input type="checkbox"/> |
|                                                                                    | <b>203 99 56 W</b> CABLE BASE S W     | <input type="checkbox"/> |

LED power supplies


# of Fixtures

|                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                    |                            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|----------------------------|
| <div><div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |                                                                                                                    | Min current   Max current  |
|                                                                                                                                                                                                                                                                                            | <b>21012 0010</b> LED POWER SUPPLY MULTI POWER<br><b>Dimtype: non-dimmable</b><br><b>Cutout dimension (mm): 50</b> | 1 <input type="checkbox"/> |
|                                                                                                                                                                                                                                                                                            | <b>21012 0021</b> LED POWER SUPPLY MULTI POWER DIM1<br><b>Dimtype: 1-10V</b><br><b>Cutout dimension (mm): 54</b>   | 1 <input type="checkbox"/> |


# DELTALIGHT


## LASS-OH! L330-6 93034


24819 9320 B



|                                                                                  |                                                     |                            |
|----------------------------------------------------------------------------------|-----------------------------------------------------|----------------------------|
|  | <b>21012 0035</b> LED POWER SUPPLY MULTI POWER DIM5 | 1 <input type="checkbox"/> |
| Dimtype: DALI                                                                    |                                                     |                            |
| Cutout dimension (mm): 54                                                        |                                                     |                            |

| Power box                                                                                                                                                                                                                                                                                                                                                                  | # of Fixtures             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| <div><div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> | Min current   Max current |

|                                                                                  |                                         |                            |
|----------------------------------------------------------------------------------|-----------------------------------------|----------------------------|
|  | <b>24814 0010 B</b> LASS-OH! POWERBOX B | 1 <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                         |                            |

|                                                                                   |                                              |                            |
|-----------------------------------------------------------------------------------|----------------------------------------------|----------------------------|
|  | <b>24814 0011 B</b> LASS-OH! POWERBOX DIM1 B | 1 <input type="checkbox"/> |
| Dimtype: 1-10V                                                                    |                                              |                            |





|                                                                                    |                                              |                            |
|------------------------------------------------------------------------------------|----------------------------------------------|----------------------------|
|  | <b>24814 0015 B</b> LASS-OH! POWERBOX DIM5 B | 1 <input type="checkbox"/> |
| Dimtype: DALI                                                                      |                                              |                            |

| Coversets                                                                          |                                                                 |
|------------------------------------------------------------------------------------|-----------------------------------------------------------------|
|  | <b>204 00 62 ANO</b> COVERSET R 62 ANO <input type="checkbox"/> |
|                                                                                    | <b>204 00 62 B</b> COVERSET R 62 B <input type="checkbox"/>     |
|                                                                                    | <b>204 00 62 W</b> COVERSET R 62 W <input type="checkbox"/>     |
|  | <b>204 00 90 ANO</b> COVERSET R 90 ANO <input type="checkbox"/> |
|                                                                                    | <b>204 00 90 B</b> COVERSET R 90 B <input type="checkbox"/>     |

# DELTALIGHT

## LASS-OH! L330-6 93034

24819 9320 B


|                                                                                     |                              |                    |                          |
|-------------------------------------------------------------------------------------|------------------------------|--------------------|--------------------------|
|                                                                                     | <b><u>204 00 90 W</u></b>    | COVERSET R 90 W    | <input type="checkbox"/> |
|     | <b><u>204 00 100 ANO</u></b> | COVERSET R 100 ANO | <input type="checkbox"/> |
|                                                                                     | <b><u>204 00 100 B</u></b>   | COVERSET R 100 B   | <input type="checkbox"/> |
|                                                                                     | <b><u>204 00 100 W</u></b>   | COVERSET R 100 W   | <input type="checkbox"/> |
|    | <b><u>204 62 62 ANO</u></b>  | COVERSET S 62 ANO  | <input type="checkbox"/> |
|                                                                                     | <b><u>204 62 62 B</u></b>    | COVERSET S 62 B    | <input type="checkbox"/> |
|                                                                                     | <b><u>204 62 62 W</u></b>    | COVERSET S 62 W    | <input type="checkbox"/> |
|  | <b><u>204 80 80 ANO</u></b>  | COVERSET S 80 ANO  | <input type="checkbox"/> |
|                                                                                     | <b><u>204 80 80 B</u></b>    | COVERSET S 80 B    | <input type="checkbox"/> |
|                                                                                     | <b><u>204 80 80 W</u></b>    | COVERSET S 80 W    | <input type="checkbox"/> |
|  | <b><u>204 90 90 ANO</u></b>  | COVERSET S 90 ANO  | <input type="checkbox"/> |
|                                                                                     | <b><u>204 90 90 B</u></b>    | COVERSET S 90 B    | <input type="checkbox"/> |
|                                                                                     | <b><u>204 90 90 W</u></b>    | COVERSET S 90 W    | <input type="checkbox"/> |

# DELTALIGHT

## LASS-OH! L330-6 93034

24819 9320 B


### Suspension parts



**328 10 01** SUSPENSION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



**15225 0340 B** SUSPENSION ST B


☐

Cutout dimension (mm): 27

**15225 0340 W** SUSPENSION ST W

☐

### Electric connection parts



**328 10 03** CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



**15225 0360 B** CONNECTION ST B


☐

Cutout dimension (mm): 43


**15225 0360 W** CONNECTION ST W

☐

### Light altering devices



**24814 0020 B** JIHA! S B

☐

**24814 0030 B** JIHA! R B

☐

# DELTALIGHT

## LASS-OH! L330-6 93034

24819 9320 B

Notes: