





KIX II 930

13533 9300 A

AVAILABLE IN
ALU GREY 13533 9300 A
ANTHRACITE 13533 9300 N



 [View on website](#)




General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1.1
ADJUSTABILITY	0° to 90° swiveling
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC
Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	120°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	602lm // 6,7W // 90lm/W
Accessories	

KAP KIX
HONEYCOMB KIX

For detailed installation instructions, please consult the manual : [13533_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Light altering devices



232 10 00 N KAP KIX N

☐



232 10 03 N HONEYCOMB KIX N

☐

Notes: