




SPY 52 HE 93020 ADM DIM5

19801 9325 B

AVAILABLE IN
BLACK 19801 9325 B
FULL WHITE 19801 9325 FW
WHITE 19801 9325 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	LENS FL-20° 3F MULTI DIMMABLE POWER ADAPTER 350mA

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K / 945lm
TM-30 VALUES	rf: 96 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	945lm // 6W // 157lm/W
LED TECHNICS (LUMINAIRE)	765lm // 6,9W // 111lm/W

Remarks
High Efficacy : > 100lm/W

Requirements
SPY 52 TUBE TRACK 3F DIM

For detailed installation instructions, please consult the manual : [19801_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Finish your product

	19810 0100 B	SPY 52 TUBE B	☐
	19810 0100 FBR	SPY 52 TUBE FBR	☐
	19810 0100 FG	SPY 52 TUBE FG	☐
	19810 0100 GC	SPY 52 TUBE GC	☐
	19810 0100 W	SPY 52 TUBE W	☐

COMPATIBLE TRACKS

TRACK 3F DIM H				Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m	1.6 kg	 
200 14 420	TRACK 3F DIM H 2m	2000 m	3.2 kg	 
200 14 430	TRACK 3F DIM H 3m	3000 m	4.8 kg	 
TRACK 3F DIM IN				Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m	1.2 kg	 
200 13 420	TRACK 3F DIM IN 2m	2000 m	2.4 kg	 
200 13 430	TRACK 3F DIM IN 3m	3000 m	3.5 kg	 
TRACK 3F DIM ON				Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m	1.1 kg	  
200 12 420	TRACK 3F DIM ON 2m	2000 m	2.1 kg	  
200 12 430	TRACK 3F DIM ON 3m	3000 m	3.1 kg	  

DELTALIGHT

SPY 52 HE 93020 ADM DIM5

19801 9325 B

Notes: