OBIN ON



Introducing Obin, a cutting-edge lighting solution that embodies our commitment to quality and innovation. Based on the patented ERS (Ex-Centriq Rotation System) and equipped with flat lenses, Obin fuses ultimate flexibility with supreme user comfort in a minimalistic surface mounted lighting fixture.
By adjusting the rounded backside - using the ERS system - Obin is 360° rotatable and 45° tiltable without the need of an additional hinge. On the frontside, the sleek lenses create a sense of depth without the need of real physical space.

Specification	
LED Aperture:	3"-⅜
Adjustability:	0° - 45° / 360°
Rating:	Damp

Performance	
CRI / TM-30 (3000K):	90 / Rf: 90 / Rg: 99
SDCM:	1
LED Maintenance:	L90B10>50,000h
*High Power:	13.3W / 2 x 13.3W

Delivered Lumens	**2700K**		**3000K**		**3500K**	
**Optics:	**MS**	**MD**	**MS**	**MD**	**MS**	**MD**
Obin On:	1217	1258	1272	1315	1318	1362
Obin On 2:	2434	2515	2544	2629	2636	2724

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: OBN2-HPMS27A-B-GC-MKINCD14-120

Luminaire	Size	Power*	Optic**	CCT	Function	Finish	Inner Finish	Installation	Application	Controls***
OBN OBIN ON	**1** Single Spot	**HP** High Power	**MS** Medium Narrow Spot 24° **MD** Medium Spot 36°	**27** 2700K **30** 3000K **35** 3500K	**A** Adjustable	**B** Black **BRA** Brushed Aluminum **BRAT** Brushed Anthracite **BRG** Brushed Gold **BROB** Brushed Old Bronze **W** White	**B** Black **DC** Dark Chromed **FBR** Flemish Bronze **FG** Flemish Gold **GC** Gold Colored **W** White	**MK** Mud kit into drywall over 4" junction box **PRB** Black coverplate for 4" junction box **PRW** White coverplate for 4" junction box	**INC** Integral Power Supply	**D14-120** FE ELV dim 120V / 0-10V dim 120/277V
	2 Double Spot	**HP** High Power	**MS** Medium Narrow Spot 24° **MD** Medium Spot 36°	**27** 2700K **30** 3000K **35** 3500K	**A** Adjustable	**B** Black **W** White				


*** Contact factory for Dali, DMX, or other dimming options.


Related Products


Spy 90 (similar scale), M-Obin, Deep Ringo (downlight with same finish options), Spy 39 (spotlight with same finish options)


Finish Options


OBIN ON






BLACK


BRUSHED ALUMINUM



BRUSHED ANTHRACITE



BRUSHED GOLD



BRUSHED OLD BRONZE


WHITE

OBIN ON 2





BLACK


WHITE


LENS DETAIL

INNER FINISH



For Application M20H


BLACK


DARK CHROMED



FLEMISH BRONZE


FLEMISH GOLD


GOLD COLORED


WHITE


Accessories




HONEYCOMB 75
19810 0110 B

Photometric Data

OBIN




MS 24°



MD 36°


Installation Options

MK - MUD KIT 1



Requires 4" junction box


PRB/PRW COVERPLATE R 132



BLACK or WHITE
Requires 4" junction box

Used with SIZE 1

PRB/PRW COVERPLATE R 133



BLACK or WHITE
Requires 4" junction box

Used with SIZE 2

Driver Options

D14

- Dimming Control: Phase Control or -10V
- Dimming Range: 1-100%
- Dim to off: yes
- Power Factor @ Full Load: >0.9
- Efficiency @ Full Load: ≥90
- THD @ Full Load: <20%

Dimmer Compatibility Phase

- Leviton IP1106-1LZ / 6631-2
- Leviton DVELV-303P / MAELV-600

Dimmer Compatibility 0-10V

- Leviton IP710-DLZ
- Leviton DVTV-XX

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.