



PARTOU FLAT 93036 SI

25219 9320 B



AVAILABLE IN

BLACK 25219 9320 B

FLEMISH BRONZE 25219 9320 FBR

FLEMISH GOLD 25219 9320 FG

WHITE 25219 9320 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	50
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	LENS FL-36° EXCLLED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	36°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	519lm // 6,7W // 78lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

Options

PLASTERKIT 101

For detailed installation instructions, please consult the manual : [25219_XXX0_HAND.pdf](#)

DELTALIGHT

PARTOU FLAT 93036 S1


25219 9320 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	 202 11 19 - PLASTERKIT 101 Required
 Wood	-
 Concrete + plaster	 202 11 19 - PLASTERKIT 101 Required
 Lintel + plaster	 202 11 19 - PLASTERKIT 101 Required
 Hollow-core slab + plaster	 202 11 19 - PLASTERKIT 101 Required
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

Emergency units

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B ☐
Cutout dimension (mm): 27	
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W ☐

LED power supplies








of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

PARTOU FLAT 93036 S1

25219 9320 B

	300 90 91 LED POWER SUPPLY 350mA-DC / 15W	2(1)	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			
	300 90 108 U LED POWER SUPPLY 350mA-DC / 8W	1	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 47			
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	3(2)	☐
Dimtype: 1-10V or push button			
Cutout dimension (mm): 55			
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2)	☐
Dimtype: DALI			
Cutout dimension (mm): 55			
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
Dimtype: mains (phase cut-off)			
Cutout dimension (mm): 50			
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2	☐
Dimtype: mains (phase cut-off)			
Cutout dimension (mm): 50			
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	2(2)	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 60			

Plasterkits

	202 11 19 PLASTERKIT 101		☐
Cutout dimension (mm): 80 x 180			

Notes:

DELTALIGHT

PARTOU FLAT 93036 S1

25219 9320 B