
DELTALIGHT




# M20/M26H - SPY 391 92720 MDL

**REFERENCE** 23315 9220 BRG

AVAILABLE IN
**BLACK** 23315 9220 B
**BRUSHED ALU** 23315 9220 BRA
**BRUSHED ANTHRACITE** 23315 9220 BRAT
**BRUSHED COPPER** 23315 9220 BRCU
**BRUSHED GOLD** 23315 9220 BRG
**BRUSHED OLD BRONZE** 23315 9220 BROB
**FLEMISH BRONZE** 23315 9220 FBR
**FLEMISH GOLD** 23315 9220 FG
**GOLD COLOURED** 23315 9220 GC
**PIANO BLACK** 23315 9220 PB
**WHITE** 23315 9220 W







View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.3 |
| **ADJUSTABILITY** | 0° to 85° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-20°<br>EXCL.LED POWER SUPPLY 48V-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | MDL = 1-10V or DALI or push button |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, EPD |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 20° |
| **LED TECHNICS (LIGHT SOURCE)** | 1041lm // 8,6W // 121lm/W |
| **LED TECHNICS (LUMINAIRE)** | 849lm // 9,9W // 86lm/W |

**Remarks**

**Take a look at our MAGNETIC PROFILES movie**

**Requirements**

SPY 39 TUBE or VISOR 39
LED POWER SUPPLY 48V-DC

**Options**

DIMMABLE MODULATOR

DELTALIGHT

# M20/M26H - SPY 391 92720 MDL

23315 9220 BRG

For detailed installation instructions, please consult the manual : **23315_XXX0_HAND.pdf**


## FINISH YOUR SPECIFICATION

### Current supply

**# of Fixtures**

**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**21032 0030** SMART 48 MODULATOR PLUG-IN WD — 19


**Dimtype: WDL = wireless dimmable**

### SMART 48

**# of Fixtures**


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 90 011** SMART 48 MODULATOR DIM9 — 19

**Dimtype: 1-10V or DALI or push button**




**300 90 012** SMART 48 MODULATOR WD — 19


**Dimtype: WDL = wireless dimmable**

### LED power supplies

**# of Fixtures**

**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 10

**Dimtype: non-dimmable**

DELTALIGHT


# M20/M26H - SPY 391 92720 MDL

23315 9220 BRG




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 24


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 10

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**





**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 20

**Dimtype: non-dimmable**


**Cutout dimension (mm): 40**

## Light altering devices




**24144 0030 B** VISOR 39 B

## Finish your product




**24144 0010 B** SPY 39 TUBE B

**24144 0010 FBR** SPY 39 TUBE FBR

**24144 0010 FG** SPY 39 TUBE FG

**24144 0010 GC** SPY 39 TUBE GC

**24144 0010 W** SPY 39 TUBE W




**24144 0070** SPY 39 TUBE SBL


# M20/M26H - SPY 391 92720 MDL

23315 9220 BRG


## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H FLOOR

Available Colours





**29323 920W** SLM26H F MDL WD





**29323 930W** SLM26H F MDL WD

### SHIFTLINE M26H profile


Available Colours





**23359 0000** SLM26H - PROFILE




**23359 0010** SLM26H - PROFILE 1m




**23359 0020** SLM26H - PROFILE 2m




**23359 0030** SLM26H - PROFILE 3m

### SPLITLINE M20 ST profile

Available Colours




**23397 0000** SPM20 ST - PROFILE




**23397 0020** SPM20 ST - PROFILE 2m








**23397 0030** SPM20 ST - PROFILE 3m

DELTALIGHT

# M20/M26H - SPY 391 92720 MDL

23315 9220 BRG

| SPLITLINE M20 profile | Available Colours |
|---|---|
|  **420 20 10 00** SPM20 - PROFILE 1m | |
|  **420 20 20 00** SPM20 - PROFILE 2m | |
|  **420 20 30 00** SPM20 - PROFILE 3m | |
|  **23301 0000** SPM20 - PROFILE B | |

Notes: