



BOXY R 93033 DIM8

251 70 811 932 ED8 B-FG

AVAILABLE IN


BLACK-BLACK 251 70 811 932 ED8 B-B

BLACK-FLEMISH BRONZE 251 70 811 932 ED8 B-FBR

BLACK-FLEMISH GOLD 251 70 811 932 ED8 B-FG

WHITE-BLACK 251 70 811 932 ED8 W-B

WHITE-WHITE 251 70 811 932 ED8 W-W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP53
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	852lm // 9,9W // 86lm/W

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

For detailed installation instructions, please consult the manual : [251_70_811_XXX_ED8_HAND.pdf](#)

BOXY R 93033 DIM8

251 70 811 932 ED8 B-FG

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

☐

Light altering devices



Ø40



Ø45

251 70 03 01 B BOXY HONEYCOMB B

☐

251 70 03 01 W BOXY HONEYCOMB W

☐

Ø40



Ø45

251 70 03 04 B BOXY SOFTENING LENS B

☐

251 70 03 04 W BOXY SOFTENING LENS W

☐

Ø40



Ø45

251 70 03 05 B BOXY GLASS SBL B

☐

251 70 03 05 W BOXY GLASS SBL W

☐

Notes: