



OML50 - LED ARRAY DU HE 656mm 930 DIM5

31039 9305

 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
INFORMATION	CLUSTER DOWN: 2780lm/m CLUSTER UP: 1932lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1824lm UP: LED cluster 8,2W / CRI>90 (R9: 50) / 3000K / 1267lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 1824lm // 11,1W // 164lm/W UP: 1267lm // 8,2W // 155lm/W

Options

WIRELESS CONTROL DIM5

Notes: