



OML50 - LED ARRAY DU HE 656mm 940

31039 9400



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.8
INFO	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT
Elektrische info	
ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 11,1W / CRI>90 (R9: 50) / 4000K / 1901lm UP: LED cluster 8,2W / CRI>90 (R9: 50) / 4000K / 1322lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 1901lm // 11,1W // 171lm/W UP: 1322lm // 8,2W // 162lm/W

Notes: