





MIKALINE L198 930

30612 9300 GC

AVAILABLE IN

BLACK 30612 9300 B

GOLD COLOURED 30612 9300 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PLUG-IN-48V CABLE 11cm black EXCL.LED POWER SUPPLY 48V-DC connection max.140W (3A)

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED FLEX 27W / CRI>90 / 3000K / 2138lm
LED TECHNICS (LIGHT SOURCE)	2138lm // 27W // 79lm/W
LED TECHNICS (LUMINAIRE)	1125lm // 31W // 36lm/W

Requirements

LED POWER SUPPLY 48V-DC (Remote)
POWERBOX 48V-DC PLUG-IN




Options

MIKALINE - JUNCTION / FIXATION
MIKALINE - CABLE SUSPENSION
PLUG-IN 48V CABLE
CONNECTION CLIP 1 x PLUG-IN 48V
CEILING BASE PLUG-IN 48V





For detailed installation instructions, please consult the manual : [30612_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	30610 0100 PLUG-IN 48V CABLE 11cm black	☐
	30610 0110 PLUG-IN 48V CABLE 1,5m black	☐
	30610 0120 PLUG-IN 48V CABLE 3m black	☐
	30610 0140 B CONNECTION CLIP 1 x PLUG-IN 48V B	☐
Cutout dimension (mm): 51		


LED power supplies

	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	☐
Dimtype: non-dimmable		
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	☐
Dimtype: non-dimmable		
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		

DELTALIGHT

MIKALINE L198 930

30612 9300 GC




21032 0331 LED POWER SUPPLY 48V-DC / 90W DIM1

☐

Dimtype: 1-10V

Cutout dimension (mm): 75




21032 0345 LED POWER SUPPLY 48V-DC / 90W DIM5

☐

Dimtype: DALI

Cutout dimension (mm): 75




30610 0190 POWER ADAPTER 48V-DC / 60W PLUG-IN

☐

Dimtype: non-dimmable

Power box



30610 0170 B POWERBOX 48V-DC / 100W PLUG-IN B

☐

Dimtype: non-dimmable

Suspension parts



30610 0080 B MIKALINE - CABLE SUSPENSION SINGLE 1,6m B

☐

Fixation components



30610 0010 C MIKALINE - JUNCTION 2 FLEX SET C

☐



30610 0020 C MIKALINE - JUNCTION 3 FLEX C

☐

DELTALIGHT

MIKALINE L198 930

30612 9300 GC

	30610 0030 C MIKALINE - JUNCTION 4 FLEX C	☐
	30610 0040 C MIKALINE - JUNCTION 2 HINGE C	☐
	30610 0050 C MIKALINE - FIXATION SIDE SET C	☐
	30610 0060 B MIKALINE - FIXATION SPACER FLEX SET B	☐
	30610 0070 C MIKALINE - FIXATION H/V FLEX C	☐
	30610 0090 B MIKALINE - FIXATION SPACER SET B	☐
	30610 0180 B MIKALINE - SPACER 90° 2 SET B	☐

Ceiling bases

	30610 0150 B CEILING BASE 3 x PLUG-IN 48V B	☐
	30610 0160 B CEILING BASE 1 x PLUG-IN 48V B	☐

DELTALIGHT

MIKALINE L198 930

30612 9300 GC

Notes: