




SPYCO CLIP AC 93033 DIM8

19918 9328 W

AVAILABLE IN
BLACK 19918 9328 B
WHITE 19918 9328 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Semi-recessed
CUTOUT SHAPE/SIZE (MM)	round - 51
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	REFLECTOR FL-33° BLACK version: INCL.SPY TUBE S B / WHITE version: INCL.SPY TUBE S W

Electrical info

ELECTRICAL	230V / 50-60Hz
CLASS	I
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	AC LED array 8W / CRI>90 (R9: 54) / 3000K / 630lm
TM-30 VALUES	rf: 91 / Rg: 98
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80B10 > 67000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	630lm // 8W // 79lm/W
LED TECHNICS (LUMINAIRE)	477lm // 8W // 60lm/W

Accessories

SPY TUBE S







For detailed installation instructions, please consult the manual : [19918_XXX8_HAND.pdf](#)

DELTALIGHT

SPYCO CLIP AC 93033 DIM8

19918 9328 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Concrete	-
 Hollow-core slab	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

Finish your product

	414 02 00 B	SPY TUBE S B	<input type="checkbox"/>
	414 02 00 FBR	SPY TUBE S FBR	<input type="checkbox"/>
	414 02 00 FG	SPY TUBE S FG	<input type="checkbox"/>
	414 02 00 MMAT	SPY TUBE S MMAT	<input type="checkbox"/>
	414 02 00 SG	SPY TUBE S SG	<input type="checkbox"/>
	414 02 00 W	SPY TUBE S W	<input type="checkbox"/>

DELTALIGHT

SPYCO CLIP AC 93033 DIM8

19918 9328 W

Notes: