



## OONO P70 930 DIM8

29616 9308 B

AVAILABLE IN  
**BLACK** 29616 9308 B  
**ANTHRACITE** 29616 9308 N



 [View on website](#)



### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Surface mounted
<b>INGRESS PROTECTION</b>	IP54
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK04
<b>WEIGHT (KG)</b>	3.6
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	E

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 52) / 3000K/1089lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1089lm // 8,6W // 127lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	599lm // 9,9W // 61lm/W

### Options

PLATE 7  
 PIN 12  
 CBOX  
 IP68 CONNECTION KIT  
 IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : [29616\\_XXX8\\_HAND.pdf](#)

# DELTALIGHT


## OONO P70 930 DIM8

29616 9308 B

### FINISH YOUR SPECIFICATION

#### Waterproof connection parts


---



**216 12 00** CBOX

Cutout dimension (mm): 142 x 142

---




**216 12 01** IP68 CONNECTION KIT



**216 12 02** IP68 CONNECTOR 3P

#### Pins and plates for bollards

---



**229 01 12** PIN 12



**229 02 07** PLATE 7

Notes: