



Image may differ from the actual product
Consult drawing for correct size and structure



INFORM 40 SQ 320 PDS DOWN-UP 93063 DIM5

30734 9335 B-B

DISPONIBLE EN

NOIR-NOIR 30734 9335 B-B

BLANC-NOIR 30734 9335 W-B



[Voir sur le site Web](#)



Informations générales	
EMPLACEMENT	interieur
INSTALLATION	Plafond Suspendu
INDICE DE PROTECTION	IP20
POIDS (KG)	5.3
ORIENTATION	non réglable
INFORMATIONS	INCL.PRESENCE & DAYLIGHT SENSOR INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m
Informations électriques	
ÉLECTRIQUE	220-240V / 0 50-60Hz
CLASSE	I
ALIMENTATION	YES
TYPE DIM	DALI
CLASSE D'ÉNERGIE	E
Info Source lumineuse	
LIGHTSOURCE NAME	LED
SOURCE DE LUMIÈRE	DOWN (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm UP (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm Or DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm UP: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm
VALEURS TM-30	Rf: 92 / Rg: 100 DOWN: rf: 92 / Rg: 100 UP: rf: 92 / Rg: 100
SDCM	SDCM3
GROUPE DE RISQUE	RG1
LM80	L80 > 60000
BEAMANGLE	63°
TECHNIQUES LED (SOURCE LUMINEUSE)	DOWN (HO): 6989lm // 48,4W // 145lm/W UP (HO): 6989lm // 48,4W // 145lm/W Or DOWN: 5069lm // 32,6W // 155lm/W UP: 5069lm // 32,6W // 155lm/W
TECHNIQUES LED (LUMINAIRE)	DOWN (HO): 4836lm // 55,7W // 87lm/W UP (HO): 4603lm // 55,7W // 83lm/W Or DOWN: 3507lm // 37,5W // 94lm/W UP: 3338lm // 37,5W // 89lm/W

DELTALIGHT

INFORM 40 SQ 320 PDS DOWN-UP 93063 DIM5

30734 9335 B-B


Références optionnelles

CABLE BASE R / S

Pour des instructions d'installation détaillées, veuillez consulter le manuel : [30734_XXX5_HAND.pdf](#)

TERMINEZ VOTRE SPÉCIFICATION

le cable d'alimentation



41 **203 99 55 ANO** CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐

41 **203 99 56 ANO** CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐


203 99 56 W CABLE BASE S W

☐

divers



26510 0010 PDS REMOTE CONTROL

☐

26510 0020 PDS SENSOR PROGRAMMER

☐

DELTALIGHT

INFORM 40 SQ 320 PDS DOWN-UP 93063 DIM5

30734 9335 B-B

Notes: