





## INFORM 40 SQ 320 PDS DOWN-UP 93063 DIM5

30734 9335 B-B

AVAILABLE IN

**BLACK-BLACK** 30734 9335 B-B

**WHITE-BLACK** 30734 9335 W-B



[View on website](#)



| General info                |                                                                                                                                                                                                                                                                  |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOCATION                    | indoor                                                                                                                                                                                                                                                           |
| INSTALLATION                | Ceiling Suspended                                                                                                                                                                                                                                                |
| INGRESS PROTECTION          | IP20                                                                                                                                                                                                                                                             |
| WEIGHT (KG)                 | 5.3                                                                                                                                                                                                                                                              |
| ADJUSTABILITY               | non adjustable                                                                                                                                                                                                                                                   |
| INFORMATION                 | INCL.PRESENCE & DAYLIGHT SENSOR<br>INCL.DIMMABLE LED POWER SUPPLY (DALI DT6)<br>Power selection to be set on driver<br>INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m<br>INCL.1 x CABLE 5 x 0,75mm <sup>2</sup> 1,6m                                                |
| Electrical info             |                                                                                                                                                                                                                                                                  |
| ELECTRICAL                  | 220-240V / 0 50-60Hz                                                                                                                                                                                                                                             |
| CLASS                       | I                                                                                                                                                                                                                                                                |
| POWER SUPPLY                | YES                                                                                                                                                                                                                                                              |
| DIM TYPE                    | DALI                                                                                                                                                                                                                                                             |
| ENERGY CLASS                | E                                                                                                                                                                                                                                                                |
| Lightsource info            |                                                                                                                                                                                                                                                                  |
| LIGHTSOURCE NAME            | LED                                                                                                                                                                                                                                                              |
| LIGHTSOURCE                 | DOWN (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm<br>UP (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm<br>Or<br>DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm<br>UP: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm |
| TM-30 VALUES                | Rf: 92 / Rg: 100<br>DOWN: rf: 92 / Rg: 100<br>UP: rf: 92 / Rg: 100                                                                                                                                                                                               |
| SDCM                        | SDCM3                                                                                                                                                                                                                                                            |
| RISKGROUP                   | RG1                                                                                                                                                                                                                                                              |
| LM80                        | L80 > 60000                                                                                                                                                                                                                                                      |
| BEAMANGLE                   | 63°                                                                                                                                                                                                                                                              |
| LED TECHNICS (LIGHT SOURCE) | DOWN (HO): 6989lm // 48,4W // 145lm/W<br>UP (HO): 6989lm // 48,4W // 145lm/W<br>Or<br>DOWN: 5069lm // 32,6W // 155lm/W<br>UP: 5069lm // 32,6W // 155lm/W                                                                                                         |
| LED TECHNICS (LUMINAIRE)    | DOWN (HO): 4836lm // 55,7W // 87lm/W<br>UP (HO): 4603lm // 55,7W // 83lm/W<br>Or<br>DOWN: 3507lm // 37,5W // 94lm/W<br>UP: 3338lm // 37,5W // 89lm/W                                                                                                             |

DELTALIGHT

INFORM 40 SQ 320 PDS DOWN-UP 93063 DIM5

30734 9335 B-B


Options

CABLE BASE R/S

For detailed installation instructions, please consult the manual : [30734\\_XXX5\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO

CABLE BASE R ANO

☐

203 99 55 B

CABLE BASE R B

☐

203 99 55 W

CABLE BASE R W

☐



203 99 56 ANO

CABLE BASE S ANO

☐

203 99 56 B

CABLE BASE S B


☐

203 99 56 W

CABLE BASE S W

☐


Other



26510 0010

PDS REMOTE CONTROL

☐



26510 0020

PDS SENSOR PROGRAMMER

☐

# DELTALIGHT

## INFORM 40 SQ 320 PDS DOWN-UP 93063 DIM5

30734 9335 B-B

Notes: