



## SUPERLOOP HC SBL OVAL M 927

20571 9200 B


AVAILABLE IN

**BLACK** 20571 9200 B

**FLEMISH BRONZE** 20571 9200 FBR

**FLEMISH GOLD** 20571 9200 FG

**WHITE** 20571 9200 W



[View on website](#)



### General info

|                           |                                                                                                                                             |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                                      |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                                           |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                                        |
| <b>WEIGHT (KG)</b>        | 4.5                                                                                                                                         |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                              |
| <b>INFORMATION</b>        | INCL.PC SBL<br>EXCL.LED POWER SUPPLY 900-1200mA-DC<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m<br>INCL.1 x CABLE 2 x 0.75mm <sup>2</sup> |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | E                         |
| <b>CERTIFICATES</b> | CB, ENEC, EPD             |

### Lightsource info

|                                    |                                                                |
|------------------------------------|----------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                            |
| <b>LIGHTSOURCE</b>                 | LED cluster 36,3-49,5W / CRI>90 (R9: 59) / 2700K / 5217-6845lm |
| <b>SDCM</b>                        | SDCM3                                                          |
| <b>LM80</b>                        | L70 > 20000                                                    |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 6845lm // 49,5W // 138lm/W                                     |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 4113lm // 56,9W // 72lm/W                                      |

### Requirements

LED POWER SUPPLY 900 / 1200mA-DC DIM  
SUPERLOOP POWERBOX H 900mA  
SUPERLOOP POWERBOX H 1200mA

### Options

CABLE BASE R / S  
COVERSET R 62-90-100 / S 62-80-90  
CONNECTION ST / CONNECTION TRIMLESS  
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20571\\_XXX0\\_HAND.pdf](#)


DELTA LIGHT

SUPERLOOP HC SBL OVAL M 927

20571 9200 B

FINISH YOUR SPECIFICATION

Current supply



|                                                                                  |                                       |                          |
|----------------------------------------------------------------------------------|---------------------------------------|--------------------------|
|  | <b>203 99 55 ANO</b> CABLE BASE R ANO | <input type="checkbox"/> |
|                                                                                  | <b>203 99 55 B</b> CABLE BASE R B     | <input type="checkbox"/> |
|                                                                                  | <b>203 99 55 W</b> CABLE BASE R W     | <input type="checkbox"/> |
|  | <b>203 99 56 ANO</b> CABLE BASE S ANO | <input type="checkbox"/> |
|                                                                                  | <b>203 99 56 B</b> CABLE BASE S B     | <input type="checkbox"/> |
|                                                                                  | <b>203 99 56 W</b> CABLE BASE S W     | <input type="checkbox"/> |

Power box

# of Fixtures

Min current | Max current


 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

|                                                                                    |                                                             |   |                          |
|------------------------------------------------------------------------------------|-------------------------------------------------------------|---|--------------------------|
|  | <b>321 55 312 ED1 B</b> SUPERLOOP POWERBOX H8 1200mA DIM1 B | 1 | <input type="checkbox"/> |
|                                                                                    | <b>321 55 312 ED1 W</b> SUPERLOOP POWERBOX H8 1200mA DIM1 W | 1 | <input type="checkbox"/> |
|  | <b>20548 0015 B</b> SUPERLOOP POWERBOX H9 900mA DIM5 B      | 1 | <input type="checkbox"/> |
|                                                                                    | <b>20548 0015 W</b> SUPERLOOP POWERBOX H9 900mA DIM5 W      | 1 | <input type="checkbox"/> |

# DELTALIGHT

## SUPERLOOP HC SBL OVAL M 927

20571 9200 B



|                                                                                  |                                                         |   |                          |
|----------------------------------------------------------------------------------|---------------------------------------------------------|---|--------------------------|
|  | <b>20548 0025 B</b> SUPERLOOP POWERBOX H9 1200mA DIM5 B | 1 | <input type="checkbox"/> |
|                                                                                  | <b>20548 0025 W</b> SUPERLOOP POWERBOX H9 1200mA DIM5 W | 1 | <input type="checkbox"/> |

Dimtype: DALI

### LED power supplies

# of Fixtures  
Min current | Max current

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



|                                                                                    |                                                         |   |                          |
|------------------------------------------------------------------------------------|---------------------------------------------------------|---|--------------------------|
|    | <b>300 90 129</b> LED POWER SUPPLY 900mA-DC / 60W DIM5  | 1 | <input type="checkbox"/> |
|                                                                                    | <b>300 90 130</b> LED POWER SUPPLY 1200mA-DC / 60W DIM5 | 1 | <input type="checkbox"/> |
|  | <b>300 90 132</b> LED POWER SUPPLY 1200mA-DC / 70W DIM1 | 1 | <input type="checkbox"/> |

Dimtype: DALI  
Cutout dimension (mm): 84

Dimtype: DALI  
Cutout dimension (mm): 95

Dimtype: 1-10V  
Cutout dimension (mm): 80

### Coversets

|                                                                                    |                                        |                          |
|------------------------------------------------------------------------------------|----------------------------------------|--------------------------|
|  | <b>204 00 62 ANO</b> COVERSET R 62 ANO | <input type="checkbox"/> |
|                                                                                    | <b>204 00 62 B</b> COVERSET R 62 B     | <input type="checkbox"/> |
|                                                                                    | <b>204 00 62 W</b> COVERSET R 62 W     | <input type="checkbox"/> |
|  | <b>204 00 90 ANO</b> COVERSET R 90 ANO | <input type="checkbox"/> |

# DELTALIGHT

## SUPERLOOP HC SBL OVAL M 927

20571 9200 B

|                                                                                     |                              |                    |                          |
|-------------------------------------------------------------------------------------|------------------------------|--------------------|--------------------------|
|                                                                                     | <b><u>204 00 90 B</u></b>    | COVERSET R 90 B    | <input type="checkbox"/> |
|                                                                                     | <b><u>204 00 90 W</u></b>    | COVERSET R 90 W    | <input type="checkbox"/> |
|     | <b><u>204 00 100 ANO</u></b> | COVERSET R 100 ANO | <input type="checkbox"/> |
|                                                                                     | <b><u>204 00 100 B</u></b>   | COVERSET R 100 B   | <input type="checkbox"/> |
|                                                                                     | <b><u>204 00 100 W</u></b>   | COVERSET R 100 W   | <input type="checkbox"/> |
|    | <b><u>204 62 62 ANO</u></b>  | COVERSET S 62 ANO  | <input type="checkbox"/> |
|                                                                                     | <b><u>204 62 62 B</u></b>    | COVERSET S 62 B    | <input type="checkbox"/> |
|                                                                                     | <b><u>204 62 62 W</u></b>    | COVERSET S 62 W    | <input type="checkbox"/> |
|  | <b><u>204 80 80 ANO</u></b>  | COVERSET S 80 ANO  | <input type="checkbox"/> |
|                                                                                     | <b><u>204 80 80 B</u></b>    | COVERSET S 80 B    | <input type="checkbox"/> |
|                                                                                     | <b><u>204 80 80 W</u></b>    | COVERSET S 80 W    | <input type="checkbox"/> |
|  | <b><u>204 90 90 ANO</u></b>  | COVERSET S 90 ANO  | <input type="checkbox"/> |
|                                                                                     | <b><u>204 90 90 B</u></b>    | COVERSET S 90 B    | <input type="checkbox"/> |
|                                                                                     | <b><u>204 90 90 W</u></b>    | COVERSET S 90 W    | <input type="checkbox"/> |

# DELTALIGHT

## SUPERLOOP HC SBL OVAL M 927

20571 9200 B

### Suspension parts

|                                                                                   |                                             |                          |
|-----------------------------------------------------------------------------------|---------------------------------------------|--------------------------|
|   | <b>328 10 01</b> SUSPENSION TRIMLESS O.F.A. | <input type="checkbox"/> |
| Cutout dimension (mm): 62 (CONCRETE: 102)                                         |                                             |                          |
|  | <b>15225 0340 B</b> SUSPENSION ST B         | <input type="checkbox"/> |
| Cutout dimension (mm): 27                                                         |                                             |                          |
|                                                                                   | <b>15225 0340 W</b> SUSPENSION ST W         | <input type="checkbox"/> |

### Electric connection parts

|                                                                                     |                                             |                          |
|-------------------------------------------------------------------------------------|---------------------------------------------|--------------------------|
|   | <b>328 10 03</b> CONNECTION TRIMLESS O.F.A. | <input type="checkbox"/> |
| Cutout dimension (mm): 62 (CONCRETE: 102)                                           |                                             |                          |
|  | <b>15225 0360 B</b> CONNECTION ST B         | <input type="checkbox"/> |
| Cutout dimension (mm): 43                                                           |                                             |                          |
|                                                                                     | <b>15225 0360 W</b> CONNECTION ST W         | <input type="checkbox"/> |

Notes: