




D-LINER 19 INF LOC2 286 94058 RD

32021 9420 B

AVAILABLE IN
BLACK 32021 9420 B



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	12 x REFLECTOR 58° EXCL.LED POWER SUPPLY 150mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male green

Electrical info	
CLASS	III
ENERGY CLASS	C

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 5W / CRI>90 / 4000K / 904lm
BEAMANGLE	58°
LED TECHNICS (LIGHT SOURCE)	904lm // 5W // 180lm/W
LED TECHNICS (LUMINAIRE)	769lm // 5,8W // 134lm/W

Requirements	
LED POWER SUPPLY SET LOC PARALLEL	

Options	
CONNECTING CABLE LOC PARALLEL	

For detailed installation instructions, please consult the manual : [32021_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu WEC	-

FINISH YOUR SPECIFICATION

Emergency units		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
Dimtype: DALI	32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5	1
	32010 1200 T CONNECTOR LOC PARALLEL	
	32010 1310 CONNECTING CABLE LOC PARALLEL 1m	
	32010 1320 CONNECTING CABLE LOC PARALLEL 2m	
	32010 1330 CONNECTING CABLE LOC PARALLEL 3m	
	32010 1340 CONNECTING CABLE LOC PARALLEL 4m	
	32010 1350 CONNECTING CABLE LOC PARALLEL 5m	

D-LINER 19 INF LOC2 286 94058 RD


32021 9420 B

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



32010 0075 LED POWER SUPPLY SET LOC PARALLEL 150mA / 35W DIM5

1

Dimtype: DALI

Notes: