



## ENTERO RD-M IP TW 96518



28416 9010 GC

AVAILABLE IN

**BLACK** 28416 9010 B

**FULL WHITE** 28416 9010 FW

**GOLD COLOURED** 28416 9010 GC



[View on website](#)



### General info

|                                           |                                                                    |
|-------------------------------------------|--------------------------------------------------------------------|
| <b>LOCATION</b>                           | indoor                                                             |
| <b>INSTALLATION</b>                       | Ceiling Recessed                                                   |
| <b>CUTOUT SHAPE/SIZE (MM)</b>             | round - 92                                                         |
| <b>RECESSED DEPTH (MM)</b>                | 145                                                                |
| <b>THICKNESS OF MOUNTING SURFACE (MM)</b> | max.16                                                             |
| <b>INGRESS PROTECTION</b>                 | IP44/20                                                            |
| <b>WEIGHT (KG)</b>                        | 0.415                                                              |
| <b>ADJUSTABILITY</b>                      | 0° to 20° swiveling, 355° rotatable                                |
| <b>INFORMATION</b>                        | REFLECTOR SP-18°<br>EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | E                         |
| <b>CERTIFICATES</b> | CB, ENEC, EPD             |

### Lightsource info

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                   |
| <b>LIGHTSOURCE</b>                 | LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                      |
| <b>SDCM</b>                        | SDCM2                                                 |
| <b>RISKGROUP</b>                   | RG1                                                   |
| <b>LM80</b>                        | L90B10 > 50000                                        |
| <b>BEAMANGLE</b>                   | 18°                                                   |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1087lm // 9W // 121lm/W                               |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 725lm // 10,4W // 70lm/W                              |

### Requirements

LED POWER SUPPLY 500mA-DC TW

### Options

ENTERO RD-M MOUNTING SET S2

For detailed installation instructions, please consult the manual : [28416\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT


## ENTERO RD-M IP TW 96518

28416 9010 GC

### CEILING COMPATIBILITY

| Ceiling Type                                                                                                  | Mounting Kit                                                                                                                                       |
|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
|  System ceiling               | -                                                                                                                                                  |
|  Plasterboard                 | -                                                                                                                                                  |
|  Stucanet                     | -                                                                                                                                                  |
|  Wood                         | -                                                                                                                                                  |
|  Concrete                     |  28500 0200 - ENTERO RD-M MOUNTING SET S2 <span>Required</span>   |
|  Concrete + plaster           |  28500 0200 - ENTERO RD-M MOUNTING SET S2 <span>Required</span>   |
|  Lintel + plaster           |  28500 0200 - ENTERO RD-M MOUNTING SET S2 <span>Required</span> |
|  Hollow-core slab           |  28500 0200 - ENTERO RD-M MOUNTING SET S2 <span>Required</span> |
|  Hollow-core slab + plaster |  28500 0200 - ENTERO RD-M MOUNTING SET S2 <span>Required</span> |
|  Stretched ceiling          | -                                                                                                                                                  |

### FINISH YOUR SPECIFICATION

| LED power supplies                                                                                                                                                                                                                                                                                                                                      | # of Fixtures          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <div> # of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div> |                        |
| <div><div><b>21012 0355</b> LED POWER SUPPLY 500mA-DC 2CH TW DIM5<br/>Dimtype: DALI<br/>Cutout dimension (mm): 85</div></div>                                                                                                                                         | 2 <input type="text"/> |


# DELTALIGHT

## ENTERO RD-M IP TW 96518

28416 9010 GC

### Mounting set S2

---



**28500 0200** ENTERO RD-M MOUNTING SET S2



Notes: