

ENTERO RD-M TRIMLESS WALLWASH TW 965



28469 9000 B

AVAILABLE IN

BLACK 28469 9000 B

GOLD COLOURED 28469 9000 GC

WHITE 28469 9000 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	95
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.16
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WALLWASH EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	884lm // 10,4W // 85lm/W

Requirements

MOUNTING KIT ENTERO ROUND M
LED POWER SUPPLY 500mA-DC TW (Remote)
















For detailed installation instructions, please consult the manual : [28469_XXX0_HAND.pdf](#)

DELTALIGHT

ENTERO RD-M TRIMLESS WALLWASH TW 965

28469 9000 B


CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Plasterboard	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stucanet	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Concrete + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Lintel + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Hollow-core slab + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stretched ceiling	 28400 0140 - MOUNTING KIT ENTERO RD-M WSC	Required
	 28400 0080 - MOUNTING KIT ENTERO RD-M CSC	Required


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

2

Dimtype: DALI

Cutout dimension (mm): 85

Mounting kits



28400 0020 MOUNTING KIT ENTERO RD-M O.F.A.


Cutout dimension (mm): 127

DELTALIGHT

ENTERO RD-M TRIMLESS WALLWASH TW 965

28469 9000 B

Mounting kits stretched ceiling



28400 0080 MOUNTING KIT ENTERO RD-M CSC



28400 0140 MOUNTING KIT ENTERO RD-M WSC



Notes: