
DELTALIGHT




OONO F40 927

REFERENCE 29617 9200 B

AVAILABLE IN
BLACK 29617 9200 B
ANTHRACITE 29617 9200 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,2W / CRI>90 (R9: 60) / 2700K / 2009lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2009lm // 17,2W // 117lm/W
LED TECHNICS (LUMINAIRE)	767lm // 19,8W // 39lm/W

Options

CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : **29617_XXX0_HAND.pdf**


DELTALIGHT

OONO F40 927

29617 9200 B

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142

☐



216 12 01 IP68 CONNECTION KIT

☐



216 12 02 IP68 CONNECTOR 3P

☐

Notes: