



## HEDRA ON 2 93033 DIM1

473 231 812 932 ED1 BBR-B



AVAILABLE IN

**BLACK-BLACK** 473 231 812 932 ED1 B-B

**BLACK BRONZE-BLACK** 473 231 812 932 ED1 BBR-B

**GOLD COLORED-BLACK** 473 231 812 932 ED1 GC-B

**WHITE-WHITE** 473 231 812 932 ED1 W-W



[View on website](#)



### General info

|                           |                                                                 |
|---------------------------|-----------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                          |
| <b>INSTALLATION</b>       | Ceiling Surface mounted, Wall Surface mounted                   |
| <b>INGRESS PROTECTION</b> | IP20                                                            |
| <b>WEIGHT (KG)</b>        | 0.9                                                             |
| <b>ADJUSTABILITY</b>      | 0° to 90° swiveling, 355° rotatable                             |
| <b>INFORMATION</b>        | 2 x REFLECTOR FL-33°<br>INCL.DIMMABLE LED POWER SUPPLY 350mA-DC |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | 1-10V              |
| <b>ENERGY CLASS</b> | C                  |
| <b>CERTIFICATES</b> | CB, EAC, ENEC, RCM |

### Lightsource info

|                                    |                                                        |
|------------------------------------|--------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                    |
| <b>LIGHTSOURCE</b>                 | 2 x (LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm) |
| <b>TM-30 VALUES</b>                | Rf: 90 / Rg: 99                                        |
| <b>SDCM</b>                        | SDCM1                                                  |
| <b>RISKGROUPE</b>                  | RG1                                                    |
| <b>LM80</b>                        | L90B10 > 50000                                         |
| <b>BEAMANGLE</b>                   | 33°                                                    |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1574lm // 11,6W // 135lm/W                             |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 790lm // 13,3W // 59lm/W                               |

### Requirements

VIZIR TUBE

### Accessories

VIZIR HONEYCOMB

VIZIR SOFTENING LENS


For detailed installation instructions, please consult the manual : [473 231 812 XXX ED1 HAND.pdf](#)

HEDRA ON 2 93033 DIM1

473 231 812 932 ED1 BBR-B

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




**300 90 016 ED1** WIRELESS CONTROL 5A DIM1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 86

☐

Light altering devices




**473 03 01 B** VIZIR HONEYCOMB B

☐

**473 03 04** VIZIR SOFTENING LENS

☐

Finish your product



**473 01 00 B** VIZIR TUBE B

☐

**473 01 00 FBR** VIZIR TUBE FBR

☐

**473 01 00 FG** VIZIR TUBE FG

☐

**473 01 00 W** VIZIR TUBE W

☐

Notes: