
DELTALIGHT




# SOLI - 66 93045 Q-DIM

**REFERENCE** 27125 933Q W

AVAILABLE IN
**BLACK** 27125 933Q B
**WHITE** 27125 933Q W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.5 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 360° rotatable |
| **INFORMATION** | REFLECTOR WFL-45°<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 18° & 30° available |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | Qbus dim |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, LCA |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 21W / CRI>90 (R9: 52) / 3000K / 2463lm |
| **TM-30 VALUES** | Rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 45° |
| **LED TECHNICS (LIGHT SOURCE)** | 2463lm // 21W // 117lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1690lm // 24,2W // 70lm/W |

**Requirements**

SPY 66 TUBE
LED POWER SUPPLY 48V-DC

**Accessories**

HONEYCOMB 57
SPREAD LENS 57
LINEAR SPREAD LENS 57
SOFTENING LENS 57
GLASS SBL 57

DELTALIGHT

# SOLI - 66 93045 Q-DIM

27125 933Q W

For detailed installation instructions, please consult the manual : **27125_XXXQ_HAND.pdf**


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

**Min current | Max current**





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 4

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 10


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 4

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**





**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 8


**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**

### Light altering devices




**24611 0150 B** HONEYCOMB 57 SINGLE USE B





**24611 0160** GLASS SBL 57


DELTALIGHT

# SOLI - 66 93045 Q-DIM


27125 933Q W





**24611 0170** LINEAR SPREAD LENS 57




**24611 0190** SOFTENING LENS 57





**24611 0200** SPREAD LENS 57




**24611 0210 B** HONEYCOMB 57 DOUBLE USE B

## Finish your product




**24611 0100 B** SPY 66 TUBE B

**24611 0100 FBR** SPY 66 TUBE FBR

**24611 0100 FG** SPY 66 TUBE FG

**24611 0100 GC** SPY 66 TUBE GC

**24611 0100 W** SPY 66 TUBE W

## Replaceable reflector / lens




**24611 0220** SPY 66 REFLECTOR 18°

DELTALIGHT

## SOLI - 66 93045 Q-DIM

27125 933Q W





**24611 0230** SPY 66 REFLECTOR 30°



**24611 0240** SPY 66 REFLECTOR 45°

## COMPATIBLE COMPOSABLES

| SOLISCAPE profile | Available Colours |
|---|---|
|  **27111 0020** SOLI - PROFILE 2m | |
|  **27111 0030** SOLI - PROFILE 3m | |

Notes: