



INFORM R1 DOWN 93048

26811 9320 W-B

AVAILABLE IN



BLACK-BLACK 26811 9320 B-B

BLACK-FLEMISH GOLD 26811 9320 B-FG

FLEMISH GOLD-BLACK 26811 9320 FG-B

WHITE-BLACK 26811 9320 W-B

WHITE-WHITE 26811 9320 W-W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° EXCLLED POWER SUPPLY 700mA-DC
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	C
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 22,9W / CRI>90 (R9: 50) / 3000K / 3504lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	3504lm // 22,9W // 153lm/W
LED TECHNICS (LUMINAIRE)	2926lm // 26,3W // 111lm/W

Requirements

LED POWER SUPPLY 700mA-DC DIM (Remote)

Options

SUSPENSION SET 30 2x0,75 1,6m


CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

For detailed installation instructions, please consult the manual : [26811_XXX0_HAND.pdf](#)



FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

of Fixtures






 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	1 ☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1 ☐

DELTALIGHT

INFORM R1 DOWN 93048

26811 9320 W-B



Coversets

	<u>204 00 62 ANO</u>	COVERSET R 62 ANO	☐
	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐

DELTALIGHT

INFORM R1 DOWN 93048

26811 9320 W-B

	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

Suspension parts

	<u>15225 0300 B</u>	SUSPENSION SET 30 2x0,75 1,6m B	☐
	<u>15225 0300 W</u>	SUSPENSION SET 30 2x0,75 1,6m W	☐

Electric connection parts

	<u>15225 0360 B</u>	CONNECTION ST B	☐
		Cutout dimension (mm): 43	
	<u>15225 0360 W</u>	CONNECTION ST W	☐

Notes: