



M26L - SPY 391 92740 DIM5

23259 9235 BRC

AVAILABLE IN

NEGRO 23259 9235 B

ALU CEPILLADO 23259 9235 BRA

ANTRACITA CEPILLADO 23259 9235 BRAT

COBRE CEPILLADO 23259 9235 BRCU

ORO CEPILLADO 23259 9235 BRG

BRONCE VIEJO CEPILLADO 23259 9235 BROB

FLEMISH BRONZE 23259 9235 FBR

FLEMISH GOLD 23259 9235 FG

ORO COLOREADO 23259 9235 GC

NEGRO PIANO 23259 9235 PB

BLANCO 23259 9235 W



[View on website](#)



General info

LOCATION	interior
INSTALLATION	Sistemas de baja tensión Montado en sistemas de baja tensión
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° giratorio, 360° orientable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	con DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	844lm // 9,9W // 85lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23259_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Fuente de Alimentación LED		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: no dimerizable	10	
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: no dimerizable	24	
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: no dimerizable Cutout dimension (mm): 40	10	
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: no dimerizable Cutout dimension (mm): 40	20	
Dispositivos de modificación de Luz		
 24144 0030 B VISOR 39 B		

DELTALIGHT

M26L - SPY 391 92740 DIM5

23259 9235 BRG

Termina tu producto



24144 0010 B SPY 39 TUBE B

7

24144 0010 FBR SPY 39 TUBE FBR

7

24144 0010 FG SPY 39 TUBE FG

9

24144 0010 GC SPY 39 TUBE GC

7

24144 0010 W SPY 39 TUBE W

9




24144 0070 SPY 39 TUBE SBL

9


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



DELTALIGHT

M26L - SPY 391 92740 DIM5

23259 9235 BRG

SHIFTLINE M35R profile		Available Colours
	23375 0000 SLM35R - PROFILE	
	23375 0010 SLM35R - PROFILE 1m	
	23375 0020 SLM35R - PROFILE 2m	
	23375 0030 SLM35R - PROFILE 3m	

Notes: