





SOLI - 66 93030 DIM5

REFERENCE 27123 9325 W

AVAILABLE IN
BLACK 27123 9325 B
WHITE 27123 9325 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 18° & 45° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 21W / CRI>90 (R9: 52) / 3000K / 2463lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	2463lm // 21W // 117lm/W
LED TECHNICS (LUMINAIRE)	1697lm // 24,2W // 70lm/W

Requirements	
SPY 66 TUBE	
LED POWER SUPPLY 48V-DC	

Accessories	
HONEYCOMB 57	
SPREAD LENS 57	
LINEAR SPREAD LENS 57	
SOFTENING LENS 57	
GLASS SBL 57	

DELTALIGHT

SOLI - 66 93030 DIM5

27123 9325 W

For detailed installation instructions, please consult the manual : [27123_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

4


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

10

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

4

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W

8


Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



24611 0150 B HONEYCOMB 57 SINGLE USE B




24611 0160 GLASS SBL 57


DELTALIGHT

SOLI - 66 93030 DIM5


27123 9325 W




24611 0170 LINEAR SPREAD LENS 57

☐

24611 0190 SOFTENING LENS 57

☐


24611 0200 SPREAD LENS 57

☐

24611 0210 B HONEYCOMB 57 DOUBLE USE B

☐

Finish your product



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

24611 0100 FG SPY 66 TUBE FG

☐

24611 0100 GC SPY 66 TUBE GC

☐

24611 0100 W SPY 66 TUBE W

☐

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°

☐

DELTALIGHT

SOLI - 66 93030 DIM5

27123 9325 W





24611 0230 SPY 66 REFLECTOR 30°



24611 0240 SPY 66 REFLECTOR 45°



COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
  27111 0020 SOLI - PROFILE 2m	
  27111 0030 SOLI - PROFILE 3m	

Notes: