



SPY 39 ON SOFT 93020

24175 9020 PB

AVAILABLE IN

NOIR 24175 9020 B

ALU BROSSÉ 24175 9020 BRA

ANTHRACITE BROSSÉ 24175 9020 BRAT

CUIVRE BROSSÉ 24175 9020 BRCU

OR BROSSÉ 24175 9020 BRG

BRONZE VIEUX BROSSÉ 24175 9020 BROB

FLEMISH BRONZE 24175 9020 FBR



FLEMISH GOLD 24175 9020 FG

ENTIÈREMENT BLANC 24175 9020 FW

COULEUR OR 24175 9020 GC

NOIR PIANO 24175 9020 PB

BLANC 24175 9020 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° à 85° inclinable, 355° rotatif
INFORMATION	REFLECTOR FL-20° EXCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F
CERTIFICATION	LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	508lm // 6,9W // 74lm/W

Requirements

SPY 39 TUBE


LED POWER SUPPLY 350mA-DC DIM

Options

COVERSET R 90-100

For detailed installation instructions, please consult the manual : **24175_XXX0_HAND.pdf**

les batteries de secours



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27


7

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

7

of Fixtures

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC /15W DIM1

Dimtype: 1 à 10 V

Cutout dimension (mm): 30

2

7




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC /15W DIM5

Dimtype: DALI

Cutout dimension (mm): 45

2

7




300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC /15W MDL

Dimtype: non dimmable

Cutout dimension (mm): 30

2

7




300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC /15W WDL

Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 45

2

7



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

Dimtype: fin de phase ou bouton poussoir

Cutout dimension (mm): 56











2

7

DELTALIGHT

SPY 39 ON SOFT 93020


24175 9020 PB

	<u>300 90 63</u> LED POWER SUPPLY MULTI-POWER DIM9	4(4) ☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
Cutout dimension (mm): 82		
	<u>300 90 64</u> LED POWER SUPPLY MULTI-POWER DIM7	3(2) ☐
Dimtype: 1 à 10 V ou bouton poussoir		
Cutout dimension (mm): 72		
	<u>300 90 67</u> LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	2 ☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
	<u>300 90 68</u> LED POWER SUPPLY MULTI-POWER DIM5	2(2) ☐
Dimtype: DALI		
Cutout dimension (mm): 72		
	<u>300 90 69</u> LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) ☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
Cutout dimension (mm): 84		
	<u>300 90 124</u> LED POWER SUPPLY MULTI-POWER DIM7	2(2) ☐
Dimtype: 1 à 10 V ou bouton poussoir		
Cutout dimension (mm): 55		
	<u>300 90 125</u> LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2) ☐
Dimtype: DALI		
Cutout dimension (mm): 55		
	<u>21012 0021</u> LED POWER SUPPLY MULTI POWER DIM1	3 ☐
Dimtype: 1 à 10 V		
Cutout dimension (mm): 54		
	<u>21012 0035</u> LED POWER SUPPLY MULTI POWER DIM5	3 ☐
Dimtype: DALI		
Cutout dimension (mm): 54		
	<u>21012 004W</u> LED POWER SUPPLY MULTI-POWER WDL	4(4) ☐
Dimtype: WDL = dimmable sans fil		
Cutout dimension (mm): 84		

DELTALIGHT

SPY 39 ON SOFT 93020

24175 9020 PB



21012 005W


LED POWER SUPPLY MULTI-POWER COMPACT WDL

3

☐

Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 54



21012 0268


LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2

☐

Dimtype: fin de phase

Cutout dimension (mm): 50



21012 0298


LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2

☐

Dimtype: fin de phase

Cutout dimension (mm): 48



21012 0308


LED POWER SUPPLY 350mA / 7,35W DIM8

1

☐

Dimtype: fin de phase

Cutout dimension (mm): 40



21032 0295

LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5


2

☐

Dimtype: DALI

Cutout dimension (mm): 30

les sets pour recouvrement plafond



204 00 100 ANO COVERSET R 100 ANO

☐

204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐

Terminez votre produit



24144 0010 B SPY 39 TUBE B

☐

24144 0010 FBR SPY 39 TUBE FBR

☐

DELTALIGHT

SPY 39 ON SOFT 93020

24175 9020 PB

	<u>24144 0010 FG</u>	SPY 39 TUBE FG	☐
	<u>24144 0010 GC</u>	SPY 39 TUBE GC	☐
	<u>24144 0010 W</u>	SPY 39 TUBE W	☐
	<u>24144 0070</u>	SPY 39 TUBE SBL	☐

Notes: