



COMPO M 93020

9 15727 9320 B


AVAILABLE IN

BLACK 9 15727 9320 B

CHROMED 9 15727 9320 C

DARK CHROMED 9 15727 9320 DC

WHITE 9 15727 9320 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 110
RECESSED DEPTH (MM)	105
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.256
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,5W / CRI>90 (R9: 52) / 3000K / 1378lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1378lm // 12,5W // 110lm/W
LED TECHNICS (LUMINAIRE)	791lm // 14,4W // 55lm/W

Requirements	
LED POWER SUPPLY 700 mA - DC	

Accessories	
COMPO M HONEYCOMB SINGLE USE B	
COMPO M LINEAR SPREAD LENS	
COMPO M SPREAD LENS	
COMPO M SOFTENING LENS	
COMPO M GLASS SBL	

For detailed installation instructions, please consult the manual : [9 15727 XXX0 HAND.pdf](#)

DELTALIGHT

COMPO M 93020

9 15727 9320 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	 15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
	 15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	 15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
	 15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	 15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 3100

LED POWER SUPPLY 18W NO DIM 1400mA

1->4

15710 3500

LED POWER SUPPLY MULTIPOWER 15W NO DIM 700mA

1

15710 4000

LED POWER SUPPLY MULTIPOWER 15W DIM8 700mA

1

15710 4900

LED POWER SUPPLY MULTIPOWER 20W DIM1 700mA

1

15710 5000

LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA

1->13

Dimtype: DALI

15710 5600

LED POWER SUPPLY MULTIPOWER 20W DALI DT6 700mA

1

Dimtype: DALI

Mounting kits



15710 0020 B MOUNTING KIT COMPO M TRIM B

Cutout dimension (mm): 76

15710 0020 W MOUNTING KIT COMPO M TRIM W

COMPO M 93020

9 15727 9320 B



15710 0050 MOUNTING KIT COMPO M TRIMLESS

☐

Cutout dimension (mm): 76

Light altering devices

15710 1100 B COMPO M HONEYCOMB SINGLE USE B

☐

15710 1110 COMPO M LINEAR SPREAD LENS

☐

Cutout dimension (mm): 32,5

15710 1120 COMPO M SPREAD LENS

☐

Cutout dimension (mm): 32,5

15710 1130 COMPO M SOFTENING LENS

☐

Cutout dimension (mm): 32,5

15710 1140 COMPO M GLASS SBL

☐

Cutout dimension (mm): 32,5

Notes: