



M26L - SPY 391 92740 DIM5

23259 9235 BROB

AVAILABLE IN

BLACK 23259 9235 B

BRUSHED ALU 23259 9235 BRA

BRUSHED ANTHRACITE 23259 9235 BRAT

BRUSHED COPPER 23259 9235 BRCU

BRUSHED GOLD 23259 9235 BRG

BRUSHED OLD BRONZE 23259 9235 BROB



FLEMISH BRONZE 23259 9235 FBR

FLEMISH GOLD 23259 9235 FG

GOLD COLOURED 23259 9235 GC

PIANO BLACK 23259 9235 PB

WHITE 23259 9235 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	844lm // 9,9W // 85lm/W

Remarks

Take a look at our [MAGNETIC PROFILES](#) movie






Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23259_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies		# of Fixtures		
		Min current Max current		
 55 100 90 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable			10	
 63 114 125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable			24	
 17 298 30 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40			10	
 22 392 30 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40			20	
Light altering devices				
 12 Ø35 24144 0030 B VISOR 39 B				

DELTALIGHT





M26L - SPY 391 92740 DIM5

23259 9235 BROB

Finish your product

	24144 0010 B SPY 39 TUBE B	☐
	24144 0010 FBR SPY 39 TUBE FBR	☐
	24144 0010 FG SPY 39 TUBE FG	☐
	24144 0010 GC SPY 39 TUBE GC	☐
	24144 0010 W SPY 39 TUBE W	☐
	24144 0070 SPY 39 TUBE SBL	☐





COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
	☐ ☐
	☐ ☐
	☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐
	☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐

DELTALIGHT

M26L - SPY 391 92740 DIM5

23259 9235 BROB

SHIFTLINE M35R profile		Available Colours
	23375 0000 SLM35R - PROFILE	
	23375 0010 SLM35R - PROFILE 1m	
	23375 0020 SLM35R - PROFILE 2m	
	23375 0030 SLM35R - PROFILE 3m	

Notes: