




OONO F40 930

29617 9300 B

AVAILABLE IN
BLACK 29617 9300 B
ANTHRACITE 29617 9300 N



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,2W / CRI>90 (R9: 52) / 3000K / 210lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	210lm // 17,2W // 123lm/W
LED TECHNICS (LUMINAIRE)	802lm // 19,8W // 41lm/W

Options	
CBOX	
IP68 CONNECTION KIT	
IP68 CONNECTOR 3P	

For detailed installation instructions, please consult the manual : [29617_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

☐

Cutout dimension (mm): 142 x 142



216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐

Notes: