



## MINIGRID IN TRIMLESS 2 HP 92720

100050 9210 B-B



AVAILABLE IN

**BLACK-BLACK** 100050 9210 B-B

**BLACK-WHITE** 100050 9210 B-W

**WHITE-BLACK** 100050 9210 W-B

**WHITE-WHITE** 100050 9210 W-W



[View on website](#)



### General info

|                               |                                                            |
|-------------------------------|------------------------------------------------------------|
| <b>LOCATION</b>               | indoor                                                     |
| <b>INSTALLATION</b>           | Ceiling Recessed                                           |
| <b>CUTOUT SHAPE/SIZE (MM)</b> | rectangle - KIT                                            |
| <b>RECESSED DEPTH (MM)</b>    | 160                                                        |
| <b>INGRESS PROTECTION</b>     | IP20                                                       |
| <b>WEIGHT (KG)</b>            | 1                                                          |
| <b>ADJUSTABILITY</b>          | 0° to 25° swiveling, 355° rotatable                        |
| <b>INFORMATION</b>            | 2 x REFLECTOR SP-20°<br>EXCL.LED POWER SUPPLY 500-700mA-DC |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | E                         |
| <b>CERTIFICATES</b> | CB, ENEC                  |

### Lightsource info

|                                    |                                                                    |
|------------------------------------|--------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                |
| <b>LIGHTSOURCE</b>                 | 2 x (LED array 16,3-23,2W / CRI>90 (R9: 60) / 2700K / 2209-3031lm) |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                                   |
| <b>SDCM</b>                        | SDCM1                                                              |
| <b>RISKGROUP</b>                   | RG1                                                                |
| <b>LM80</b>                        | L90B10 > 50000                                                     |
| <b>BEAMANGLE</b>                   | 20°                                                                |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 6062lm // 46,4W // 130lm/W                                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 4272lm // 53,4W // 80lm/W                                          |

### Requirements

MINIGRID IN 2 MOUNTING KIT HP  
LED POWER SUPPLY 500 / 700mA-DC DIM (Remote)

### Accessories

HONEYCOMB 72  
SOFTENING LENS 72

For detailed installation instructions, please consult the manual : [100050\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## MINIGRID IN TRIMLESS 2 HP 92720

100050 9210 B-B

### CEILING COMPATIBILITY

| Ceiling Type                                                                                    | Mounting Kit                                                                                                                      |          |
|-------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|----------|
|  System ceiling |  202 71 95 02 HP - MINIGRID IN 2 MOUNTING KIT HP | Required |
|  Plasterboard   |  202 71 95 02 HP - MINIGRID IN 2 MOUNTING KIT HP | Required |
|  Stucanet       |  202 71 95 02 HP - MINIGRID IN 2 MOUNTING KIT HP | Required |

### FINISH YOUR SPECIFICATION






#### LED power supplies

#### # of Fixtures













# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

|                                                                                    |                                                                                                                                          |                              |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
|  | <b>300 48 500 ED1</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1<br>Dimtype: 1-10V<br>Cutout dimension (mm): 30                  | 1/2 <input type="checkbox"/> |
|  | <b>300 48 500 ED5</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5<br>Dimtype: DALI<br>Cutout dimension (mm): 45                   | 1/2 <input type="checkbox"/> |
|  | <b>300 48 500 MDL</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL<br>Dimtype: non-dimmable<br>Cutout dimension (mm): 30            | 1/2 <input type="checkbox"/> |
|  | <b>300 48 500 WDL</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL<br>Dimtype: WDL = wireless dimmable<br>Cutout dimension (mm): 45 | 1/2 <input type="checkbox"/> |
|  | <b>300 48 700 ED1</b> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1<br>Dimtype: 1-10V<br>Cutout dimension (mm): 30                  | 1/2 <input type="checkbox"/> |











MINIGRID IN TRIMLESS 2 HP 92720

100050 9210 B-B

|                                                                                    |                                                                          |                           |                          |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------|---------------------------|--------------------------|
|    | <b>300 48 700 ED5</b> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 | 1/2                       | <input type="checkbox"/> |
|                                                                                    | Dimtype: DALI                                                            |                           |                          |
|                                                                                    | Cutout dimension (mm): 45                                                |                           |                          |
|    | <b>300 48 700 MDL</b> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL  | 1/2                       | <input type="checkbox"/> |
|                                                                                    | Dimtype: non-dimmable                                                    |                           |                          |
|                                                                                    | Cutout dimension (mm): 30                                                |                           |                          |
|    | <b>300 48 700 WDL</b> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL  | 1/2                       | <input type="checkbox"/> |
|                                                                                    | Dimtype: WDL = wireless dimmable                                         |                           |                          |
|                                                                                    | Cutout dimension (mm): 45                                                |                           |                          |
|    | <b>300 90 61</b> LED POWER SUPPLY MULTI-POWER DIM6                       | 1/2   1/2                 | <input type="checkbox"/> |
|                                                                                    | Dimtype: mains (phase cut-off) or push button                            |                           |                          |
|                                                                                    | Cutout dimension (mm): 56                                                |                           |                          |
|  | <b>300 90 63</b> LED POWER SUPPLY MULTI-POWER DIM9                       | 1(1)   1(1/2)             | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or DALI or push button                                    |                           |                          |
|                                                                                    | Cutout dimension (mm): 82                                                |                           |                          |
|  | <b>300 90 64</b> LED POWER SUPPLY MULTI-POWER DIM7                       | 1/2->1/2(0)   1/2->1/2(0) | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or push button                                            |                           |                          |
|                                                                                    | Cutout dimension (mm): 72                                                |                           |                          |
|  | <b>300 90 67</b> LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9    | -   1/2                   | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or DALI or push button                                    |                           |                          |
|  | <b>300 90 68</b> LED POWER SUPPLY MULTI-POWER DIM5                       | 1/2(0)   1/2(0)           | <input type="checkbox"/> |
|                                                                                    | Dimtype: DALI                                                            |                           |                          |
|                                                                                    | Cutout dimension (mm): 72                                                |                           |                          |
|  | <b>300 90 69</b> LED POWER SUPPLY MULTI-POWER HV DIM9                    | 1(1)   1(1/2)             | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or DALI or push button                                    |                           |                          |
|                                                                                    | Cutout dimension (mm): 84                                                |                           |                          |
|  | <b>300 90 124</b> LED POWER SUPPLY MULTI-POWER DIM7                      | 1/2(0)   0                | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or push button                                            |                           |                          |
|                                                                                    | Cutout dimension (mm): 55                                                |                           |                          |

MINIGRID IN TRIMLESS 2 HP 92720


100050 9210 B-B

|                                                                                    |                                                                                                                                     |                         |                          |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|-------------------------|--------------------------|
|    | <b>300 90 125</b><br>LED POWER SUPPLY MULTI-POWER MINI DIM5<br>Dimtype: DALI<br>Cutout dimension (mm): 55                           | 1/2(0)   0              | <input type="checkbox"/> |
|    | <b>300 90 135</b><br>LED POWER SUPPLY MULTI-POWER HV<br>Dimtype: non-dimmable<br>Cutout dimension (mm): 90                          | 1   1/2->1              | <input type="checkbox"/> |
|    | <b>21012 0010</b><br>LED POWER SUPPLY MULTI POWER<br>Dimtype: non-dimmable<br>Cutout dimension (mm): 50                             | 1/2   1/2               | <input type="checkbox"/> |
|    | <b>21012 0021</b><br>LED POWER SUPPLY MULTI POWER DIM1<br>Dimtype: 1-10V<br>Cutout dimension (mm): 54                               | 1/2   1/2               | <input type="checkbox"/> |
|  | <b>21012 0035</b><br>LED POWER SUPPLY MULTI POWER DIM5<br>Dimtype: DALI<br>Cutout dimension (mm): 54                                | 1/2   1/2               | <input type="checkbox"/> |
|  | <b>21012 004W</b><br>LED POWER SUPPLY MULTI-POWER WDL<br>Dimtype: WDL = wireless dimmable<br>Cutout dimension (mm): 84              | 1/2->1(1)   1/2->1(1/2) | <input type="checkbox"/> |
|  | <b>21012 005W</b><br>LED POWER SUPPLY MULTI-POWER COMPACT WDL<br>Dimtype: WDL = wireless dimmable<br>Cutout dimension (mm): 54      | 1/2   1/2               | <input type="checkbox"/> |
|  | <b>21012 0288</b><br>LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8<br>Dimtype: mains (phase cut-off)<br>Cutout dimension (mm): 55 | 0   1/2                 | <input type="checkbox"/> |
|  | <b>21012 0298</b><br>LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8<br>Dimtype: mains (phase cut-off)<br>Cutout dimension (mm): 48 | 1/2   0                 | <input type="checkbox"/> |
|  | <b>21032 0305</b><br>LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5<br>Dimtype: DALI<br>Cutout dimension (mm): 30               | 1/2                     | <input type="checkbox"/> |

# DELTALIGHT

## MINIGRID IN TRIMLESS 2 HP 92720

100050 9210 B-B




**21032 0315** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

Dimtype: DALI

Cutout dimension (mm): 30

1/2 ☐

### Mounting kits




**202 71 95 02 HP** MINIGRID IN 2 MOUNTING KIT HP

Cutout dimension (mm): 130 x 233

☐

### Light altering devices



**201 05 01 B** HONEYCOMB 72 B

☐



**201 05 04** SOFTENING LENS 72

☐

Notes: