



MINIGRID IN TRIMLESS 1 93018

100009 9310 B-B



AVAILABLE IN

BLACK-BLACK 100009 9310 B-B

BLACK-WHITE 100009 9310 B-W

WHITE-BLACK 100009 9310 W-B

WHITE-WHITE 100009 9310 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	85
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	903lm // 9,9W // 91lm/W

Requirements

MINIGRID IN 1 MOUNTING KIT
 MINIGRID IN 1 MOUNTING KIT LARGE
 CONCRETE PACK MGIT 1
 LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual : [100009_XXX0_HAND.pdf](#)

DELTALIGHT

MINIGRID IN TRIMLESS 1 93018

100009 9310 B-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 202 71 95 01 - MINIGRID IN 1 MOUNTING KIT	Required
 Plasterboard	 202 71 95 01 - MINIGRID IN 1 MOUNTING KIT	Required
 Stucanet	 202 71 95 01 - MINIGRID IN 1 MOUNTING KIT	Required
	 202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 Concrete	 202 71 96 01 - CONCRETE PACK MGIT 1	Required
 Concrete + plaster	 202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 Lintel + plaster	 202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 Hollow-core slab	 202 71 96 01 - CONCRETE PACK MGIT 1	Required
 Hollow-core slab + plaster	 202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 Stretched ceiling	 15212 0120 - MOUNTING KIT MINIGRID IN 1 CSC	Required

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

Dimtype: 1-10V

Cutout dimension (mm): 30

1



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5











Dimtype: DALI

Cutout dimension (mm): 45

1











MINIGRID IN TRIMLESS 1 93018

100009 9310 B-B

	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	1	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 30		
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	1	☐
	Dimtype: WDL = wireless dimmable		
	Cutout dimension (mm): 45		
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	1	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 30		
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	1	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 30		
	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	1	☐
	Dimtype: WDL = wireless dimmable		
	Cutout dimension (mm): 45		
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6	2 2	☐
	Dimtype: mains (phase cut-off) or push button		
	Cutout dimension (mm): 56		
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	4(4) 4(4)	☐
	Dimtype: 1-10V or DALI or push button		
	Cutout dimension (mm): 82		
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	2(1) 2(1)	☐
	Dimtype: 1-10V or push button		
	Cutout dimension (mm): 72		
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	2	☐
	Dimtype: 1-10V or DALI or push button		

MINIGRID IN TRIMLESS 1 93018






100009 9310 B-B

	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	2(2) 2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	2->6(6) 6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	3(2) 2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2(2) 2(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	3->3 2->3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	3(3) 3(3)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	3 3	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	2->3	☐


DELTALIGHT

MINIGRID IN TRIMLESS 1 93018


100009 9310 B-B

	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2	☐
Dimtype: mains (phase cut-off)			
Cutout dimension (mm): 48			
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	2(1)	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 60			
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	2(1)	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 60			
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	2	☐
Dimtype: DALI			
Cutout dimension (mm): 30			
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2	☐
Dimtype: DALI			
Cutout dimension (mm): 30			

Concrete packs

	202 71 96 01 CONCRETE PACK MGIT 1	☐
Cutout dimension (mm): 160 x 160		

Mounting kits


	202 71 95 01 MINIGRID IN 1 MOUNTING KIT	☐
Cutout dimension (mm): 130 x 130		
	202 71 95 01L MINIGRID IN 1 MOUNTING KIT LARGE	☐
Cutout dimension (mm): 200		

DELTALIGHT

MINIGRID IN TRIMLESS 1 93018

100009 9310 B-B

Mounting kits stretched ceiling



15212 0120 MOUNTING KIT MINIGRID IN 1 CSC



Notes: