



SUPERNOVA FLAT 65 PRISMATIC DOWN-UP 930



REFERENCE

20613 9300 B

AVAILABLE IN

BLACK 20613 9300 B

WHITE 20613 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	9.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.LED POWER SUPPLY 930mA (DOWN) / 500mA (UP)

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 930mA: LED cluster 37,4W / CRI>90 (R9: 68) / 3000K / 5360lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm)
TM-30 VALUES	Rf: 89 / Rg: 97 Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000 L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 930mA: 5360lm // 37,4W // 144lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 930mA: 3934lm // 43W // 91lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W

Requirements

SUSPENSION SET 25 3m
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90

DELTA LIGHT


SUPERNOVA FLAT 65 PRISMATIC DOWN-UP 930

20613 9300 B



For detailed installation instructions, please consult the manual : [20613_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	<div><div>203 99 55 ANO</div><div>CABLE BASE R ANO</div></div>	☐
	<div><div>203 99 55 B</div><div>CABLE BASE R B</div></div>	☐
	<div><div>203 99 55 W</div><div>CABLE BASE R W</div></div>	☐
	<div><div>203 99 56 ANO</div><div>CABLE BASE S ANO</div></div>	☐
	<div><div>203 99 56 B</div><div>CABLE BASE S B</div></div>	☐
	<div><div>203 99 56 W</div><div>CABLE BASE S W</div></div>	☐





Coversets

	<div><div>204 00 62 ANO</div><div>COVERSET R 62 ANO</div></div>	☐
	<div><div>204 00 62 B</div><div>COVERSET R 62 B</div></div>	☐
	<div><div>204 00 62 W</div><div>COVERSET R 62 W</div></div>	☐
	<div><div>204 00 90 ANO</div><div>COVERSET R 90 ANO</div></div>	☐

DELTALIGHT

SUPERNOVA FLAT 65 PRISMATIC DOWN-UP 930

20613 9300 B

	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐




DELTA

LIGHT

SUPERNOVA FLAT 65 PRISMATIC DOWN-UP 930

20613 9300 B

Suspension parts

	<div><div>274 97 10 B</div><div>CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B</div></div>	☐
	<div><div>274 97 10 W</div><div>CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W</div></div>	☐
	<div><div>328 25 43</div><div>SUSPENSION SET 25 3m</div></div>	☐
	<div><div>328 26 23 B</div><div>CENTRAL SUSPENSION SUPERNOVA FLAT 3m B</div></div>	☐
	<div><div>328 26 23 W</div><div>CENTRAL SUSPENSION SUPERNOVA FLAT 3m W</div></div>	☐

Electric connection parts

	<div><div>15225 0360 B</div><div>CONNECTION ST B</div></div> <div>Cutout dimension (mm): 43</div>	☐
	<div><div>15225 0360 W</div><div>CONNECTION ST W</div></div>	☐

Notes: